

**134F4159****FC-302N200T5E20H2BGCXXXSXXXAXBXCXXXDX**

Frekans Kvertörü

FC-302N200T5E20H2BGCXXXSXXXAXBXCXXXDX

VLT® AutomationDrive FC-302

(N200) 200 KW / 300 HP, Trifaze

380 - 500 VAC, IP 20 / Şasi

RFI Sınıfı A2 (C3)

Fren kesici

Grafik Lokal Kontrol Panel

Kaplama PCB, Şebeke Seçeneği yok

Son sürüm std. yazılım

Kasa Boyutu: D4H

C1 opsiyonu yok, D seçeneği yok

A Seçeneği Yok, B Seçeneği Yok

Model Koduna göre diğer seçenekler

Model kodu: FC-302N200T5E20H2BGCXXXSXXXAXBXCXXXDX

VLT® AutomationDrive, tüm standart veya servo makinelerde ya da üretim hatlarında tam kapsamlı operasyon kontrolü sunan tek bir sürücü konsepti oluşturur.

Verimlilik Verilerini Görüntüleme**PRODUCT DETAILS**

Brüt ağırlık		121 kg
Net ağırlık		116 kg
Hacim		0 l
EAN		5710107440092
VLT® AUTOMATIONDRIVE FC 300 SERIES		
Ürün Görünümü (Anahtar)	GLBL	Global (Standart)
Ürün Grubu	FC-	VLT® AutomationDrive FC-
Seri	302	302
Güç Değeri	N200	(N200) 200 KW / 300 HP
Faz	T	Trifaze
Şebeke Voltajı	5	380 - 500 VAC
Muhafaza	E20	IP 20 / Şasi
RFI Filtresi	H2	RFI Sınıfı A2 (C3)
Fren - Güvenli Duruş	B	Fren kesici
LCP	G	Grafik Lokal Kontrol Panel
Kaplama PCB	C	Kaplama PCB
Şebeke Opsiyonu	X	Şebeke Seçeneği yok
Uyarlama A	X	Standart Kablo Girişleri
Uyarlama B	X	Uyarlama yok
Yazılım Sürümü	SXXX	Son sürüm std. yazılım
Yazılım Dil Paketi	X	Standart Dil Paketi
A Opsiyonu	AX	A Seçeneği Yok
B Opsiyonu	BX	B Seçeneği Yok
C0 Opsiyonu MCO	CX	C0 seçeneği yok
C1 Opsiyonu	X	C1 opsiyonu yok

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | FC-302N200T5E20H2BGCXXXSXXXAXBXCXXXDX

PRODUCT DETAILS

C Opsiyon Yazılımı	XX	Yazılım seçeneği yok
D Opsiyonu	DX	D seçeneği yok
Kasa Boyutu	D4H	D4H
Tür Kodu Parça 1		FC-302N200T5E20H2BGC
Tür Kodu Parça 2		XXXSXXXAXBXCXXXDX
Ürün Grubu	GLBL	Global (Standard)
Güç %150 (HO) [KW]		200
Güç %110 (NO) [KW]		250
Yükseklik [mm]		1122,0
Rejen/Yük Pylş ile Yksklk [mm]		1268,0
C opsiyonu olm. genişlik [mm]		350,0
Derinlik [mm]		375,0
A/B opsiyonu ile Derinlik [mm]		375,0
kVA		274
Güç Kaybı NO [W]		5137
Güç Kaybı NO [W]		4566
Güç Kaybı HO [W]		4039
Güç Kaybı HO [W]		3575
Sürekli Akım (NO) [A]		480
Kesintili Akım (NO) [A]		528
Sürekli Akım (NO) [A]		443
Kesintili Akım (NO) [A]		487
Sürekli Akım (HO) [A]		395
Kesikli Akım (HO) [A]		592
Sürekli Akım (HO) [A]		361
Kesikli Akım (HO) [A]		542
Hesaplanan Brüt Ağırlık [kg]		125.3
Hes. Net Ağı. [kg]		125
ECCN EU		Y901
ECCN US		3A999.a
Sipariş Hattından Tesis		D401
Satıcı	ERR01	Satıcı Belirlenmiyor
Fabrika Tarafından Önerilen	ERR01	Satıcı Belirlenmiyor
Modelkodu01		FC-302N200T5E20H2BGC
Modelkodu02		XXXSXXXAXBXCXXXDX

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Aksesuarlar

Image
coming
soon

176F3527 [🔗](#)

kit,cooling,in bottom out back,d2h d4h

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

Image
coming
soon**176F3628** **Cooling Kit, in btm/out top, 1800mm D4h**Image
coming
soon**176F3626** **VLT® in back/out back cooling kit d4h**Image
coming
soon**176F3649** **Cooling Kit, in back/out back, D2h**Image
coming
soon**176F3634** **Cooling Kit, in back/out back, D4h**
kit, cooling, in back out back, 3r, d4hImage
coming
soon**176F3630** **Cooling Kit, in btm/out top, 2000mm, D4h**

Rittal option ventilation accessories for ventilation of an FC New Generation D-Frame, housing size D4h over control cabinet base and roof. Only suitable for control cabinet H 2000 mm. Contains components / assembly parts for lower and upper air ducts including seals and fastening material. Incl. Assembly drawing 177R0457

Image
coming
soon**176F3410** **VLT® drive replace adptr plate d2h d4h**

VLT® drive replace adptr plate d2h d4h

**130B7635** **VLT® Lift Controller MCO 361**

Kaldırma uygulamasına yönelik özel yazılım içeren VLT® Motion Control MCO 305

**130B7145** **VLT® SALT Controller MCO 360**

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B5646** [🔗](#)**VLT® EtherCAT MCA 124, kaplamalı**

MCA 124 Ethercat option painted The VLT® EtherCat MCA 124 option enables Connection to EtherCat-based networks via the EtherCat protocol.

The option allows an EtherCat connection with full Speed and a connection to the frequency converter with a time interval of 4 ms in both Directions. This enables the MCA124 to be used in Networks from low-power applications to Servo applications.

- EoE EtherNet over EtherCat support
- HTTP (Hypertext Transfer Protocol) for diagnosis via integrated web server
- SMTP (Single Mail Transfer Protocol) for email notification
- TCP / IP for easy access to frequency converters Configuration data via MCT 10

**130B1235** [🔗](#)**VLT® PROFINET MCA 120, kaplamalı**

MCA 120 PROFINET interface

With reinforced coating (class 3C3 / IEC 60721-3-3)

- Supports operation on PROFINET network with extensive characteristics
- DCP support for easy setting u. Communication parameters via the PLC
- on Board web-Page with Drive Status
- parameterization with the MCT10 software
- 2-port version, reduced external hardware

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1234** **VLT® Motion Control MCO 305, kaplamalı**

Integrated and programmable motion controller for VLT® AutomationDrive FC 301 and FC 302

- Adds additional functionality and flexibility as it is a freely programmable module
- Optimized for all types of positioning and synchronization applications
- Make your own program specially adapted to your application

Contains:

- synchronization (electronic shaft), positioning and electronic cam control
- 2 inputs support both stepwise and absolute encoders
- 1 encoder output (virtual master function)

10 digital inputs

- 8 digital outputs

- Sends and receives data via fieldbus interface (requires fieldbus option)
- PC software for programming and commissioning

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option,
together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option,
together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3
excepted)

Danfoss MCO options are not sold without prior advice.

Danfoss can offer help with programming / setting up MCO options.

Contact Danfoss for advice and prices.

Product group: R

**130B1245** **VLT® PROFIBUS Converter MCA113, kaplamalı**

Ensures easy and quick replacement of VLT®3000 to VLT® AutomationDrive

.

VLT® 3000 can then be replaced by VLT® AutomationDrive or

- the system Can be expanded without costly changes to the PLC program
- Flexible investment as it is easy to remove and replace option when upgrading to another fieldbus

Product group: R1

**130B1227** **VLT® Resolver Input MCB 103, kaplamalı**

Resolver extension for FC 300. Enables the connection of the following

Resolver types:

Input voltage: 4..8 Vrms

Input frequency: 2.5..15 kHz

Number of resolver poles: 2 or 4

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar



130B1220 [🔗](#)

VLT® Safe PLC I/O MCB 108, kaplamalı

Increases security and helps you meet requirement security levels

- VLT® AutomationDrive FC 302 has a safety input based on a single pole 24 V DC input

- Security in a cost-effective way

Possibility of connection to two conductor safety system

Possibility to interrupt on the plus or minus side without disturbing the sensor signal



130B1219 [🔗](#)

VLT® EtherNet IP MCA 121, kaplamalı

EtherNet/IP; ticari kullanıma hazır Ethernet'i, DeviceNet'te bulunan aynı üst katman protokolü ve nesne modeli olan Ortak Endüstriyel Protokole (CIP™) genişletir. Hat topolojisi sağlayan ve harici anahtar ihtiyacını ortadan kaldıran dahili yüksek performanslı anahtar. Daha yüksek sistem kullanılabilirliği için Aygıt Düzeyinde Halka (DLR) topolojisi. CIP™ temelinde, DeviceNet'ten EtherNet/IP'ye geçiş sırasında PLC programının tekrar kullanılmasını mümkün kılar. Dahili web sunucusu uzaktan arıza tespiti ve temel sürücü parametrelerini okuma olanağı sağlar. E-posta bildirimi, uyarı veya alarm bilgilerine hızlı erişim sağlar. Gelişmiş ağ kullanımı için Tek Noktaya Yayın ve Çok Noktaya Yayın iletişimi. En yeni standarda uyum konusunda ODVA onaylı.



130B1264 [🔗](#)

VLT® Extended Relay Card MCB 113, kplımlı

Daha fazla esneklik için 7 dijital giriş ve 2 analog çıkış ekler. 4 SPDT röle. NAMUR tavsiyelerine uygundur. Galvanik izolasyon olanağı.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1253****VLT® Position Controller MCO 351, kplmlı**

Extends the functional characteristics of the frequency converter in positioning applications

- Direct positioning via fieldbus, relative positioning, absolute positioning and touch probe positioning
- End stop handling (software and hardware)
- Mechanical brake handling (programmable hold delay)

Error handling

- Jog speed / manual operation
- None for programming, as it is pre-programmed

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice.

Danfoss can offer help with programming / setting up MCO options.

Contact Danfoss for advice and prices.

Product group: R

**130B1252****VLT® Synchronizing Ctrl. MCO 350, kplmlı**

MCO 350 - synchronous controller

Based on the MCO 305 prefabricated controller for Synchronization tasks. The adjustment takes place through parameter settings. Specific Programming skills are not required.

- 2 encoder inputs, both for incremental as well as absolute encoder
- 1 encoder output (virtual master function)
- 10 additional digital inputs
- 8 additional digital outputs
- fieldbus Communication (requires fieldbus card) with reinforced coating

**130B1246****MCA101 Profibus Option DP V0/V1 FC300**

VLT® AutomationDrive'da VLT® 5000 komutlarını emüle eden özel bir PROFIBUS opsiyonları versiyonu.

VLT® 5000, VLT® AutomationDrive ile değiştirilebilir ya da PLC programında masraflı değişiklik yapmadan mevcut bir sistem genişletilebilir. Farklı bir haberleşmeye yükseltme için, kurulu olan konvertör kolayca çıkarılır ve yeni bir opsiyonla değiştirilir. Bu, esnekliğin azalmasına yol açmadan yatırımı korur. Opsiyon, DPV1'i destekler.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1196****VLT® Modbus TCP MCA 122**

MCA 122 Modbus TCP interface Complex compatibility tests make the perfect operation in Modbus TCP systems for sure.

- On Board web-Page with Drive Status
- Parameterization with MCT10 software
- 2 port version reduces effort for external hardware (switch, cables, etc.) and allows flexible bus topologies

**130B1172****VLT® Sensor Input Card MCB 114, kplasz**

Motordaki yatakların ve sargıların sıcaklığını izleyerek motoru aşırı ısınmaya karşı korur. 2 veya 3 telli PT100/PT1000 sensörler için üç adet otomatik algılamalı sensör girişi. Bir ek analog giriş 4-20 mA.

**130B1170****LCP Panel Montaj Kiti**

Kit; tespit elemanları ve conta içerir. LCP ve kablo içermez.

**130B1212****VLT® General Purpose I/O MCB 101, kplımlı**

MCB 101 - Advanced I / O option

Expands the number of freely programmable

Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.
 - 2 analog inputs 0 - 10 V.
 - 2 digital outputs NPN / PNP switchable 24 V
 - 1 analog output 0/4 - 20 mA
- with reinforced coating

**130B1210****VLT® Relay Option MCB 105, kaplamalı**

Relay extension for FC 100 and FC 300.

Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology.

Painted version for harsh environments, easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A

**130B1208****VLT® 24V DC Supply MCB 107, kaplamalı**

Güç arızası sırasında kontrol bölümünü ve tüm kurulu opsiyonları çalışır durumda tutmak için harici bir DC beslemesi bağlayın. LCP'nin (parametre ayarı dahil) ve tüm kurulu opsiyonların şebeke bağlantısı olmadan tam olarak çalışmasını sağlar.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1205** [🔗](#)**VLT® CAN Open MCA 105, kaplamalı**

CANopen interface for FC 300. Max. Baud rate 500 kBit / s. Support that DSP402 drive profile and PDO / SDO communication. Painted version for harsh environments. Easy to retrofit thanks to modular technology.

**130B1203** [🔗](#)**VLT® Encoder Input MCB 102, kaplamalı**

Çeşitli tiplerde artımlı ve mutlak enkoderleri bağlama imkanı sağlar. Bağlı enkoder, kapalı çevrim hız kontrolünün yanı sıra kapalı çevrim motor akısı kontrolü için kullanılabilir.

**130B1202** [🔗](#)**VLT® DeviceNet MCA 104, kaplamalı**

MCA 104 - DeviceNet interface Option for FC300 and FC100 for mounting on the control card. Painted version

**130B1200** [🔗](#)**VLT® Profibus DP V1 MCA 101, kaplamalı**

Geniş çaplı uyumluluk, yüksek düzeyde kullanılabilirlik, tüm büyük PLC sağlayıcıları için destek ve gelecekteki versiyonlarla uyumluluk sağlar. Hızlı, verimli iletişim, şeffaf kurulum, gelişmiş arıza bulma ve parametrelendirme ile GSD dosyası kullanarak süreç verilerinin otomatik konfigürasyonu. PROFIBUS DP-V1, -PROFIdrive veya Danfoss FC profili durum makineleri, PROFIBUS DP-V1, Master Sınıf 1 ve 2 kullanarak çevrimsiz parametrelendirme.

**130B1387** [🔗](#)**MCB107 Extern 24VDC Option FC300****130B1386** [🔗](#)**VLT® Profibus DP V1 MCA 101, kpl., 5 adt****130B1385** [🔗](#)**VLT® Profibus DP V1 MCA101, kplmsz 5 adt****130B1272** [🔗](#)**VLT® Sensor Input Card MCB114, kaplamalı**

MCB 114 - PT100 / PT1000 option
For FC100-FC200 and FC302 (painted version)
Enables the evaluation of up to 3 PT 100 or 3 PT 1000 sensors
- Connection of 2 and 3 wire sensors
- Automatic detection of the sensor type
- Additional 4-20mA input

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1296****VLT® Modbus TCP MCA 122, kaplamalı**

Otomasyona yönelik ilk endüstriyel Ethernet tabanlı protokol. Modbus-TCP tabanlı ağlara bağlanır. Bağlantı aralığını her iki yönde 5 ms'ye kadar düşürebilmesi sayesinde, piyasadaki en hızlı çalışan Modbus TCP aygıtları arasında yer alır. Master yedekliliği için iki master arasında çalışırken değiştirebilme özelliği sunar.

**130B1164****VLT® Extended Relay Card MCB 113**

Daha fazla esneklik için 7 dijital giriş ve 2 analog çıkış ekler. 4 SPDT röle. NAMUR tavsiyelerine uygundur. Galvanik izolasyon olanağı.

**130B1135****VLT® PROFINET MCA 120, kaplamasız**

MCA 120 PROFINET interface

- Supports operation on PROFINET network with extensive properties
- DCP support for easy setting u. Communication parameters via the PLC
- On Board web-Page with Drive Status
- Parameterization with the MCT10 software
- 2 port version, reduced external hardware

**130B1134****VLT® Motion Control MCO 305, kaplamasız**

Integrated and programmable motion controller for VLT® AutomationDrive FC 301 and FC 302

- Adds additional functionality and flexibility as it is a freely programmable module
- Optimized for all types of positioning and synchronization applications
- Make your own program specially adapted to your application

Contains:

- synchronization (electronic shaft), positioning and electronic cam control
- 2 inputs support both stepwise and absolute encoders
- 1 encoder output (virtual master function)

10 digital inputs

8 digital outputs

- Sends and receives data via fieldbus interface (requires fieldbus Option)
- PC software for programming and commissioning.

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3.

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice. Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices.

Product group: R

**130B1127****VLT® Resolver Input MCB 103, kaplamasız**

Motordan hız geri bildirimini sağlamak için bir çözümleyici bağlanmasına olanak verir. Yaylı bağlantı.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1125** [🔗](#)**VLT® General Purpose I/O MCB 101, kplmsz**

MCB 101 - Advanced I / O option

Expands the number of freely programmable Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.
- 2 analog inputs 0 - 10 V.
- 2 digital outputs NPN / PNP switchable 24 V
- 1 analog output 0/4 - 20 mA

**130B1124** [🔗](#)**VLT® Control Panel LCP 101, nümerik**

Numerical control unit for FC 100 and FC 300. Allows access to all device parameters.

Quick menu for brief commissioning. Manual / auto switchover and alarm acknowledgment.

**130B1120** [🔗](#)**VLT® Safe PLC I/O MCB 108, kaplamasız**

Connection converter for FC 300 with control input for a safe stop. Allows secure connection.

Output modules with diagnostic pulse (Cross-circuit monitoring).

**130B1119** [🔗](#)**VLT® EtherNet/IP MCA 121, kaplamasız**

MCA 121 EtherNet / IP interface

- Allows connection to EtherNet / IP based Automation systems via CIP (CommonInterface Protocol)
- 2 port design reduces external components
- HTTP for diagnosis via built-in web server
- SMTP, DHCP and FTP protocols
- Prepared for parameterization with the MCT 10 software via TCP / IP
- Certified according to ODVA

**130B1117** [🔗](#)**LCP Montaj Kiti, LCP'siz**

Kit; tespit elemanları, 3 m kablo ve conta içerir. LCP içermez.

**130B1115** [🔗](#)**VLT® Encoder Input MCB 102, kaplamasız**

Çeşitli tiplerde artımlı ve mutlak enkoderleri bağlama imkanı sağlar. Bağlı enkoder, kapalı çevrim hız kontrolünün yanı sıra kapalı çevrim motor akışı kontrolü için kullanılabilir.

**130B1114** [🔗](#)**Nümerik LCP101 ile LCP Montaj Kiti, 3 m**

Kit; nümerik LCP, tespit elemanları, 3 m kablo ve conta içerir.

**130B1113** [🔗](#)**Grafik LCP102 ile LCP Montaj Kiti, 3 m**

Kit; grafik LCP, tespit elemanları, 3 m kablo ve conta içerir.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1110****VLT® Relay Option MCB 105, kaplamasız**

Relay extension for FC 100 and FC 300. Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A

**130B1153****VLT® Position Controller MCO351, kplmsz**

Extends the functional characteristics of the frequency converter in positioning applications

- Direct positioning via fieldbus, relative positioning, absolute positioning and touch probe positioning

- End stop handling (software and hardware)

- Mechanical brake handling (programmable hold delay)

Error handling

- Jog speed / manual operation

- None for programming, as it is pre-programmed

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice. Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices.

Product group: R

**130B1152****VLT® Synchronizing Contr. MCO350, kplmsz**

Senkronizasyon uygulamalarında VLT® AutomationDrive'in işlev özelliklerini genişletir ve geleneksel mekanik çözümlerin yerini alır. Hız senkronizasyonu. İşaretçi düzeltmeli ya da düzeltmesiz konum

(açı) senkronizasyonu. Çevrimiçi ayarlanabilir dişlioranı. Çevrimiçi ayarlanabilir konum (açı) ofseti. Birden fazla follower'in senkronizasyonu için sanal master işlevine sahip enkoder çıkışı.

G/Ç'ler veya haberleşme üzerinden kontrol. Giriş işlevi. Sürücünün Lokal Kontrol Paneli

aracılığıyla konfigürasyon olanağının yanı sıra durum ve veri okuma.

**130B1137****VLT® PTC Thermistor Card MCB 112, kplımlı**

ATEX: II (2) G [Ex eb Gb] [Ex db Gb] / II (2) D [Ex tb Db]

MCB 112 PTC - thermistor relay MS220DA In connection with ATEX certified explosion-proof motors for full motor protection. Certified PTC sensors are the sole protection required.

Integrable module with ATEX-compliant full thermal motor protection

1 PTB-certified PTC thermistor input

1 switch-off signal for using the Safe Stop function

1 logic output for error identification

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1077** [↗](#)**IP55/67 için Danfoss logolu LCP kör kpk.**

LCP Blindcover IP66

**130B1071** [↗](#)**6 Kutuplu Konektör, FC serisi, (10 adet)**

6-pole spring cage connectors 10 pcs

**130B1070** [↗](#)**RS485 fiş, FC serisi, (10 adet)**

10pcs RS485 connectors for FC-series.

Product group: R

**130B1108** [↗](#)**VLT® 24V DC Supply MCB 107, kaplamasız**

Güç arızası sırasında kontrol bölümünü ve tüm kurulu opsiyonları çalışır durumda tutmak için harici bir DC beslemesi bağlayın. LCP'nin (parametre ayarı dahil) ve tüm kurulu opsiyonların şebeke bağlantısı olmadan tam olarak çalışmasını sağlar.

**130B1107** [↗](#)**VLT® Control Panel LCP 102**

VLT Control Panel LCP 102

Düz metinli, aydınlatmalı grafik ekran.

Tüm dilleri ve metin karakterlerini destekler.

Kısa sürede devreye alma için hızlı menü.

Parametre grupları içim kaydetme ve kopyalama işlevi.

Tüm işlevler için çevrimiçi yardım.

**130B1103** [↗](#)**VLT® CAN Open MCA 105, kaplamasız**

Yüksek esneklik ve düşük maliyetler için standart işleme ve birlikte çalışabilirlik. Hem sürücünün kontrolüne ve durumuna yüksek öncelikli erişim (PDO İletişim) hem de çevrimsiz veriler (SDO İletişim) üzerinden tüm parametrelere erişim ile tam donanım. Birlikte çalışabilirlik için, opsiyon, DSP402 AC sürücü profiline uygulanmıştır.

**130B1102** [↗](#)**VLT® DeviceNet MCA 104, kaplamasız**

Gelişmiş Üretici/Tüketici teknolojisi sayesinde güvenli ve verimli veri işleme. ODVA'nın güçlü uygunluk testi ilkeleri, ürünlerin birlikte çalışabilmesini ve G/Ç örneği 20/70.21/71 tarafından desteklenen AC sürücü profili mevcut sistemlerle uyumluluğu sağlar.

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1100****VLT® Profibus DP V1 MCA 101**

Geniş çaplı uyumluluk, yüksek düzeyde kullanılabilirlik, tüm büyük PLC sağlayıcıları için destek ve gelecekteki versiyonlarla uyumluluk sağlar. Hızlı, verimli iletişim, şeffaf kurulum, gelişmiş arıza bulma ve parametrelendirme ile GSD dosyası kullanarak süreç verilerinin otomatik konfigürasyonu. PROFIBUS DP-V1, -PROFIdrive veya Danfoss FC profili durum makineleri, PROFIBUS DP-V1, Master Sınıf 1 ve 2 kullanarak çevrimsiz parametrelendirme.

**130B1088****IP20/21 için Danfoss logolu LCP kör kpk.****130B1490****VLT® POWERLINK MCA 123, kaplamalı**

Haberleşmenin ikinci neslini temsil eder. Otomasyon dünyasında kullanılan BT teknolojilerinin gücünün tamamını fabrika dünyasının kullanımına sunmak için endüstriyel Ethernet'in yüksek bit hızı artık kullanılabilir.

**175Z0929****LCP Kablosu, 3 m**

Cable for control panel (LCP), 3 meters
Works with the following LCP:
Alphanumeric control panel LCP3 - 175N0131
VLT® LCP 102 Graphic Display - 130B1107
VLT® LCP 101 Numeric Display - 130B1124
VLT® LCP 102 Graphic display IP66 - 130B1078
Product group: F1

Image
coming
soon**175U0009****Montaj braketi kiti, 216 x 30 x 18 mm**

Mounting angle for flatpack resistor 200W

**175N2584****VLT® EtherNet/IP MCA 121, kaplamalı**Image
coming
soon**134B5225****Uzak LCP ünitesi, 10 m**

Remote mounting kit for LCP with cover for outdoor mounting with 10 m (33 ft) cable

Image
coming
soon**134B5224****Uzak LCP ünitesi, 5 m**

Remote mounting kit for LCP with cover for outdoor mounting with 5 m (16 ft) cable

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B5223****Uzak Montaj Kiti LCP102, 3 m kablo ile**

Remote mounting kit for LCP with cover for outdoor mounting with 3 m (10 ft) cable

**134B0460****LCP 103 Wireless Communication Panel**

With VLT® Wireless Communication Panel LCP 103 you can communicate with MyDrive® Connect - an app that can be downloaded for iOS and Android based smartphones. MyDrive® Connect makes commissioning easy, monitor and maintain tasks on your frequency converter. VLT® Wireless Communication Panel LCP 103 shows the current status of the drive (On, Warning, Alarm, Wifi connection) via built-in LED. Detailed information is also available using MyDrive® Connect. Here do you have access to i.a. status, menu and alerts. You can also see graphs over the latest available data.

The new VLT® Wireless Communication Panel LCP 103 allows you to wireless communication to the following drives:

- VLT® HVAC Drive FC 102
- VLT® Refrigeration Drive FC 103
- VLT® AQUA Drive FC 202
- VLT® AutomationDrive FC 302

[!] Note!

LCP 103 only works on frequency converters produced in 2018 (White USB stik).

Product group: R1

Image
coming
soon

134B1992**Vida bağlantılı kontrol terminalleri****130B1266****VLT® MCB 115 Programlanab. G/Ç, kaplımlı**

VLT® MCB 115 programmable I / O, coated

**134B6544****Gerçek Zamanlı Saat Seçeneği D, kaplımlı**

Opsiyon yalnızca 90 kW'a kadar olan sürücülerde MKII kontrol kartları ile desteklenir ve çalışır.

Image
coming
soon

176F6761**KIT,DUCT,IN-BOTTOM/OUT-TOP,D4H**

Image
coming
soon

176F3810**KIT,MULTI WIRE,MOTOR,BB,D2H,D4H,P454**

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

Image
coming
soon**176F3855** [🔗](#)**KIT,MULTI WIRE,MAINS,BB,D2H/D4H,P454**Image
coming
soon**176F6770** [🔗](#)**KIT, COMMON MODE, T5/50M, P454**Image
coming
soon**176F3526** [🔗](#)**kit,cooling,in back out back,3r,weld,d4h**Image
coming
soon**176F3524** [🔗](#)**kit,cooling,in back out back,weld,d4h**

Back Channel cooling kit for
FC New Generation D-Frame,
Frame size D4h over backplate.
Consisting of Construction / Mounting components
for base channel and top cover all
Seals, gaskets and fasteners are supplied
Incl. assembly plan 177R0454

**130B0295** [🔗](#)**Kontrol kartı girişli aksesuar çantası**Image
coming
soon**130B4847** [🔗](#)**extension cable for lcp+communication****134B8814** [🔗](#)**VLT® PROFINET MCA120 coated 5pcs**Image
coming
soon**176F3811** [🔗](#)**KIT, COMMON MODE, T5/100M or T7, P454****134B8492** [🔗](#)**Transducer 0-10g, 4-20mA; HS-22B50**

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar



134B8493 [🔗](#)

Transducer 0-25mm/s RMS 4-20mA

CBM Transducer 0-25mm/s RMS 4-20mA



134B8494 [🔗](#)

Transducer w, temp 0-25mm/s RMS 4-20mA



134B8496 [🔗](#)

CABLE ASSY 10M, STRAIGHT SOCKET CONNETC.

Image
coming
soon

134B8497 [🔗](#)

Cable assy, M12 female connec.10m screen

Image
coming
soon

134B6883 [🔗](#)

VLT Progr. Contr. MCB 301, coated

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9414****Antifreeze Thermostat FS20, 0/+15C**

TWO-PHASE FROST PROTECTION THERMOSTATS FS-20-UW

Electronic frost protection thermostat or frost monitor with switching relay output, continuous temperature and valve output (summation output 0–10 V) and control and cascading output (0–10 V), optionally with connection for a heating element. A IP65 resistant plastic housing with display with the actual temperature, measuring range, overrange/underrange of the set switch point (frost protection temperature) and alarm indicator for "frost" or "error" (capillary breakage, overvoltage/undervoltage), quick-locking screws and a fully active sensor rod made of copper. The delivery scope includes a set of MK-05-K mounting clamps for expert attachment of the sensor rod.

Measuring range: 0...+15 °C / 32...+59 °F

Accuracy: typical ± 1 K (at +10 °C)

Sensor type: 3m Copper rod active along the entire sensor length, min. response length of 25 cm

Input: 1 x 0 -10 V control input DDC & 1 x 0 -10 V cascading input

Output: 1 x 0 -10 V output temperature (corresponding to 0...+15 °C) & 1 x 0 -10 V output valve (frost signal with control voltage and cascading)

1 x potential-free changeover contact (24 V), range of adjustment 0...+15 °C

Current consumption: max. 100 mA at 24 V DC

Load resistance: $R_L > 50$ kOhm

Ambient temperature: -15...+50 °C / 5...+122 °F (Housing) & -20...+60 °C / -4...+140 °F Sensor and capillary tube > 20 cm from the housing.

Power: 24VAC/DC ($\pm 10\%$) 24DC <2,4W

T2-IP65 plastic housing with three-line display 70x40 mm (WxH), a M16 cable glands and MK-05-K mounting clamps.

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9413****Airflow Sensor KLQ CO2 & Air Quality**

DUCT AIR QUALITY (VOC) AND CO2 SENSOR KLQ-CO2-MB

Maintenance-free duct sensor covering air quality (VOC 0...100 %), carbon dioxide (CO2 0...5000 ppm) and atmospheric pressure (hPa). The air quality is detected by a VOC sensor (mixed gas sensor for volatile organic substances) and include an automatic calibration. It determines the loading of the room air due to contaminated gases such as cigarette smoke, body perspiration, exhaled breathing air, solvent vapors, emissions etc. The air contamination can be selected into different sensitivity ranges as low, medium or high. The CO2 measurement is performed using an optical NDIR sensor (non-dispersive infra-red technology), and the detection range is calibrated for standard applications such as monitoring residential rooms and conference rooms. A microprocessor-controlled solution with factory sensor calibration, Modbus RTU connection in a resistant IP65 plastic housing with mounting flange, quick-locking screws and two M16 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

VOC Sensor: Volatile Organic Compounds sensor (metal oxide) with automatic calibration

VOC measuring range: 0...100 % air quality; referred to calibrating gas & selection of VOC sensitivities (low/medium/high)

VOC measuring accuracy: typical $\pm 20\%$ of final value (referred to calibrating gas)

CO2 Sensor: optical NDIR sensor (non-dispersive infra-red technology) including atmospheric pressure compensation (up to 1100 mbar) with manual or automatic calibration

CO2 measuring range: 0...5000 ppm

CO2 measuring accuracy: typical ± 30 ppm ($\pm 3\%$ of measured value) & temperature dependence: ± 5 ppm pro $^{\circ}\text{C}$ or $\pm 0,5\%$ of measured value pro $^{\circ}\text{C}$ (whichever is higher) & pressure dependence: $\pm 0.13\%$ per mm Hg

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC/DC ($\pm 10\%$) 24DC $<1,6\text{W}$

Operation temperature: $-10...+60\text{ }^{\circ}\text{C}$ / $14...+140\text{ }^{\circ}\text{F}$

T2-IP65 plastic housing two M20 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9412** [🔗](#)**Airflow Sensor TF65 PT1000 Temperature**

DUCT TEMPERATURE SENSOR TF 65

The TF 65 temperature measuring transducer is a PT1000 class B resistance sensor with passive output. Measuring range from $-30...+150^{\circ}\text{C}$. In a resistant IP67 plastic housing and M16 cable gland for cable connection and a straight protective measuring tube and a mounting flange.

Sensor type: PT1000 class B (DIN EN 60751) 1000ohm at $0^{\circ}\text{C} \pm 0,3\text{ K}$ Measuring range: $-30...+150^{\circ}\text{C} / -22...+302^{\circ}\text{F}$ Ambient temperature: $-20...+100^{\circ}\text{C} / -4...+212^{\circ}\text{F}$ Testing current: $< 0.6\text{ mA}$ Insulating resistance: 100 M#, at $+20^{\circ}\text{C}$ (500V DC)

Connection type: 2-wire connection

Measuring tube: stainless steel, V4A (1.4571), $\varnothing 6\text{ mm}$, inserted length = 300 mm / 11.8 in

T1-IP67 plastic housing with a M16 cable glands and a mounting flange.

Housing dimensions: 72 x 64 x 37.8 mm / 2.83 x 2.52 x 1.49 in

**134B9411** [🔗](#)**Wall Sensor AFTF Temp & Humidity**

ON-WALL- HUMIDITY- AND TEMPERATURE SENSORS AFTF-MB

Calibratable outside humidity and temperature sensor AFTF, detect the relative humidity (0...100% RH) and the temperature ($-35...+80^{\circ}\text{C}$), including various parameters in the humidity measurement. Applied in clean air and non-aggressive, dust-free environment. With a Modbus connection in a resistant IP65 plastic housing and M20 cable gland for cable connection, with quick-locking screws and an exchangeable plastic sinter filter. International SI units (default) can be changed to imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / $-35...+80^{\circ}\text{C}$ (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical $\pm 2.0\%$ (20...80 % RH) at $+25^{\circ}\text{C}$, otherwise $\pm 3.0\%$ Deviation, temperature: typical $\pm 0.4\text{ K}$ at $+25^{\circ}\text{C} / \pm 77^{\circ}\text{F}$ Zero point offset: $\pm 10\%$ RH (humidity) / $\pm 5^{\circ}\text{C}$ (temperature)Power: 24VAC ($\pm 20\%$) / 15...36VDC - 24DC $< 1,2\text{W}$ Operation temperature: $-30...+70^{\circ}\text{C} / -22...+158^{\circ}\text{F}$

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9410****Wall Sensor ATM2 Temperature**

OUTSIDE / WET ROOM TEMPERATURE SENSOR ATM2-MB

Calibratable outside temperature sensor ATM2, PT1000 measure temperature (-50...+150 °C), with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M20 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

Sensor type: PT1000 class B (DIN EN 60751)

Measuring range: - 50...+150°C / -31... +176°F

Deviation: typical ± 0.2 K at +25 °C / ± 77 °F

Zero point offset: ± 10 °C / ± 50 °F

Ambient temperature: Measuring transducer -30...+70 °C / -22... +158°F

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC (± 20%) / 15...36VDC - 24DC <1,2W

Operation temperature: -30...+70 °C / -22...+158 °F

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

Image
coming
soon**134B9409****Airflow Sensor 8147 Temp&Humidity&7000Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS ±7000PA-MB

Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature (-35...+80 °C) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max. ± 7000 Pa) with connection nozzles for pressure hose (Ø 6 mm). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / - 35...+80°C / -31... +176°F (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical ± 2.0 % (20...80 % RH) at +25°C/+77°F , otherwise ± 3.0 %

Deviation, temperature: typical ± 0.2 K at +25 °C / ± 0.4 °F at +77 °F

Pressure range: ± 7000 Pa

Accuracy: 7000 Pa/28 inWC: typical ± 105 Pa at +25 °C / ± 0.12 inWC at +77 °F

Above- # below-pressure: max. ± 50 kPa

Power: 24VAC (± 20%) / 15...36VDC - 24DC <0,2W

Operation temperature: -30...+70 °C / -22...+158 °F

Media temperature -20...+50 °C / -4...+122 °F IP65 plastic housing two

M16 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

Image
coming
soon**134B9408****Airflow Sensor 8148 Temp&Humidity&500Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS ± 500 PA-MB
Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ($-35...+80$ °C) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max. ± 500 Pa) with connection nozzles for pressure hose ($\varnothing 6$ mm). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / $-35...+80$ °C / $-31...+176$ °F (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical ± 2.0 % (20...80 % RH) at $+25$ °C/ $+77$ °F, otherwise ± 3.0 %

Deviation, temperature: typical ± 0.2 K at $+25$ °C / ± 0.4 °F at $+77$ °F

Pressure range: ± 500 Pa

Accuracy: 500 Pa/2.0 inWC: typical ± 13 Pa at $+25$ °C / ± 0.05 inWC at $+77$ °F

Above- # below-pressure: max. ± 50 kPa

Power: 24VAC (± 20 %) / 15...36VDC - 24DC $<0,2$ W

Operation temperature: $-30...+70$ °C / $-22...+158$ °F

Media temperature $-20...+50$ °C / $-4...+122$ °F IP65 plastic housing two M16 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9407****Airflow Sensor KFTF Temp & Humidity**

DUCT HUMIDITY- AND TEMPERATURE SENSORS KFTF-MB

Calibratable duct humidity and temperature sensor KFTF-T3 ($\pm 2.0\%$) with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection and a plastic sinter filter (exchangeable). Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ($-35...+80\text{ }^{\circ}\text{C}$) inside a tube, including various parameters in the humidity measurement. The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices.

International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / $-35...+80\text{ }^{\circ}\text{C}$ (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical $\pm 2.0\%$ (20...80 % RH) at $+25\text{ }^{\circ}\text{C}$, otherwise $\pm 3.0\%$

Deviation, temperature: typical $\pm 0.2\text{ K}$ at $+25\text{ }^{\circ}\text{C}$

Zero point offset: $\pm 10\%$ RH (humidity) / $\pm 5\text{ }^{\circ}\text{C}$ (temperature)

Power: 24VAC ($\pm 20\%$) / 15...36VDC - 24DC $<1,2\text{ W}$

Operation temperature: $-30...+70\text{ }^{\circ}\text{C}$ / $-22...+158\text{ }^{\circ}\text{F}$

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

**134B9406****Pressure Sensor 7227 2x7000Pa, Analog**

DUAL AIR PRESSURE SENSOR $\pm 7000\text{ Pa}$ & $\pm 7000\text{ Pa}$, ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0-10 V or 4...20 mA.

Pressure range selection: $\pm 7000\text{ Pa}$ - 0...1000Pa / 2000Pa / 3000Pa / 5000Pa / 7000Pa

Accuracy: 7000 Pa typical $\pm 105\text{ Pa}$

Zero point offset: $\pm 10\%$ of measuring range

Above- # below-pressure: max. $\pm 50\text{ kPa}$

Power: 24VAC/DC ($\pm 10\%$) $<1,3\text{ W}$,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance: R_a (ohms) = 25...450 Ohm (at I output)

Load resistance: $R_L > 15\text{ kOhm}$ (at U output)

Operation / Media temperature: $-20...+50\text{ }^{\circ}\text{C}$ / $-4...+122\text{ }^{\circ}\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9405****Pressure Sensor 7229 500/7000Pa, Analog**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 7000\text{Pa}$, ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA. Pressure range selection: $\pm 500\text{ Pa} - 0...100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$ Pressure range selection: $\pm 7000\text{ Pa} - 0...1000\text{Pa} / 2000\text{Pa} / 3000\text{Pa} / 5000\text{Pa} / 7000\text{Pa}$

Accuracy: 500 Pa typical $\pm 13\text{ Pa}$ Accuracy: 7000 Pa typical $\pm 105\text{ Pa}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ Power: 24VAC/DC ($\pm 10\%$) $< 1,3\text{W}$,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance: R_a (ohms) = 25...450 Ohm (at I output)Load resistance: $R_L > 15\text{ kOhm}$ (at U output)Operation / Media temperature: $-20...+50\text{ }^\circ\text{C} / -4...+122\text{ }^\circ\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**134B9404****Pressure Sensor 7225 2x500Pa, Analog**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 500\text{Pa}$, ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA. Pressure range selection: $\pm 500\text{ Pa} - 0...100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$

Accuracy: 500 Pa typical $\pm 13\text{ Pa}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ Power: 24VAC/DC ($\pm 10\%$) $< 1,3\text{W}$,

Output: automatically switching 0 -10 V # 4...20 mA

Working resistance: R_a (ohms) = 25...450 Ohm (at I output)Load resistance: $R_L > 15\text{ kOhm}$ (at U output)Operation / Media temperature: $-20...+50\text{ }^\circ\text{C} / -4...+122\text{ }^\circ\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9402****Pressure Sensor 7247T 2x7000Pa & PT1000**DUAL AIR PRESSURE SENSOR $\pm 7000\text{Pa}$ & $\pm 7000\text{Pa-MB}$

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ($-50\dots+150^\circ\text{C}$). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range: $\pm 7000\text{ Pa}$ and $\pm 7000\text{ Pa}$ Accuracy: 7000 Pa/28 inWC: typical $\pm 105\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.12\text{ inWC}$ at $+77^\circ\text{F}$ Linearity: $< \pm 1\%$ of final value & Temperature drift: $\pm 0.1\%$ per $^\circ\text{C}$ #
 $^\circ\text{F}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ / $\pm 200\text{ inWC}$ Power: 24VAC ($\pm 20\%$) $<0,2\text{W}$ / 15...36VDCOperation temperature: $-30\dots+70^\circ\text{C}$ / $-22\dots+158^\circ\text{F}$ Media temperature $-20\dots+50^\circ\text{C}$ / $-4\dots+122^\circ\text{F}$

T2-IP65 plastic housing with two M16 cable glands & one M12 for temperature

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**134B9401****Pressure Sensor 7249T 500/7000Pa & PT1000**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 7000\text{Pa-MB}$

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ($-50\dots+150^\circ\text{C}$). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range: $\pm 500\text{ Pa}$ and $\pm 7000\text{ Pa}$ Accuracy: 500 Pa/2.0 inWC: typical $\pm 13\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.05\text{ inWC}$ at $+77^\circ\text{F}$ Accuracy: 7000 Pa/28 inWC: typical $\pm 105\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.12\text{ inWC}$ at $+77^\circ\text{F}$ Linearity: $< \pm 1\%$ of final value & Temperature drift: $\pm 0.1\%$ per $^\circ\text{C}$ #
 $^\circ\text{F}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ / $\pm 200\text{ inWC}$ Power: 24VAC ($\pm 20\%$) $<0,2\text{W}$ / 15...36VDCOperation temperature: $-30\dots+70^\circ\text{C}$ / $-22\dots+158^\circ\text{F}$ Media temperature $-20\dots+50^\circ\text{C}$ / $-4\dots+122^\circ\text{F}$

T2-IP65 plastic housing with two M16 cable glands & one M12 for temperature

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9400** [🔗](#)**Pressure Sensor 7245T 2x500Pa & PT1000**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 500\text{Pa-MB}$

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ($-50\dots+150^\circ\text{C}$). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range: $\pm 500\text{ Pa}$ and $\pm 500\text{ Pa}$ Accuracy: $500\text{ Pa}/2.0\text{ inWC}$: typical $\pm 13\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.05\text{ inWC}$ at $+77^\circ\text{F}$ Linearity: $< \pm 1\%$ of final value & Temperature drift: $\pm 0.1\%$ per $^\circ\text{C}/^\circ\text{F}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove-/below-pressure: max. $\pm 50\text{ kPa}$ / $\pm 200\text{ inWC}$ Power: 24VAC ($\pm 20\%$) $< 0,2\text{W}$ / $15\dots 36\text{VDC}$ Operation temperature: $-30\dots+70^\circ\text{C}$ / $-22\dots+158^\circ\text{F}$ Media temperature $-20\dots+50^\circ\text{C}$ / $-4\dots+122^\circ\text{F}$

T2-IP65 plastic housing with two M16 cable glands & one M12 for temperature

Housing dimensions: $126 \times 90 \times 50\text{ mm}$ / $4.96 \times 3.54 \times 1.97\text{ in}$ **130B5601** [🔗](#)**VLT® DeviceNet converter MCA194 kplmlı**

VLT® DeviceNet converter MCA194 coated

Yedek parçalar

Image
coming
soon**176F3548** [🔗](#)**Cover DC Link Coil Large Dh Frame**

Cover DC Link Coil Large Dh Frame

**176F3540** [🔗](#)**Heatsink fan cover Dh Frames****176F3480** [🔗](#)**Power Terminal Cover IP20 D4h enclosure**

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

**176F3737** [🔗](#)**500A Current Sensor Conversion Kit**

Spare part for VLT: 500A Current Sensor Conversion Kit

**176F3329** [🔗](#)**Cable Power Card to Gate Drive D2h/D4h****176F3327** [🔗](#)**Cable Power Card to HF/RFI D2h/D4h**

Cable Power Card to HF/RFI D2h/D4h

**176F3325** [🔗](#)**Cable DC bus to Power Card D2h/D4h****176F3323** [🔗](#)**Cable Power Card to CT D2h/D4h**

For use on drives produced in week 50, 2015 or earlier.

**176F3321** [🔗](#)**Cable Power Card to Door Fan D2h/D4h****176F3319** [🔗](#)**Cable Control Card to Power Card D2h/D4h**Image
coming
soon**176F3389** [🔗](#)**Front Cover IP20 D4h enclosure****176F3386** [🔗](#)**Bus Bar Assembly CAP Bank 400V D2h/D4h**

To be used on the following frame sizes

D-frame: Drives produced before week 18, 2018 with production

site "H" indicated by the character preceding the last 3 characters of

the serial number (H188)

**176F3427** [🔗](#)**IGBT snubber kon 1250 V 1,0 UF gniş mntj**

IGBT snubber cap, mounts on brake IGBT modules

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar



176F3345 [🔗](#)
Cable Clamp 45mm Dh Frame



176F3344 [🔗](#)
Bracket Gate Drive Support D2h/D4h



176F3343 [🔗](#)
Air Baffle D4h frame



176F3336 [🔗](#)
Cable Inrush to SCR Gate D2h/D4h



176F3332 [🔗](#)
Cable Gate Drive to Inrush D2h/D4h



176F3385 [🔗](#)
Bus Bar Assembly Current Sensor D2h/D4h
For use on drives produced in week 2, 2016 or earlier.



176F3383 [🔗](#)
Bus Bar DC- Inductor to CAP Bank D2h/D4h



176F3382 [🔗](#)
Bus Bar DC+ Inductor to CAP Bank D2h/D4h



176F3381 [🔗](#)
Bus Bar DC- SCR to DC Coil D2h/D4h
Bus Bar DC- SCR to DC Coil D2h/D4h



176F3380 [🔗](#)
Bus Bar DC+ SCR to DC Coil D2h/D4h
Bus Bar DC+ SCR to DC Coil D2h/D4h

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

**176F3379** **Bus Bar SCR DC Output large D2h/D4h**

Used on the below listed drives built before week 27 of 2012.

FC-302 N200 T5

FC-102 N250 T4

FC-202 N250 T4

For drives of the above listed sizes built after week 27 of 2012 use

176F3378. See Product Note 185 for more information.

**176F3378** **Bus Bar SCR DC Output small D2h/D4h**

Used on the below listed drives built after week 27 of 2012.

FC-302 N200 T5

FC-102 N250 T4

FC-202 N250 T4

For drives of the above listed sizes built before week 27 of 2012 use

176F3379. See Product Note 185 for more information.

**176F3377** **Bus Bar SCR AC Input large D2h/D4h**

Used on the below listed drives built before week 27 of 2012.

FC-302 N200 T5

FC-102 N250 T4

FC-202 N250 T4

For drives of the above listed sizes built after week 27 of 2012 use

176F3376. See Product Note 185 for more information.

**176F3376** **Bus Bar SCR AC Input small D2h/D4h**

Used on the below listed drives built after week 27 of 2012.

FC-302 N200 T5

FC-102 N250 T4

FC-202 N250 T4

For drives of the above listed sizes built before week 27 of 2012 use

176F3377. See Product Note 185 for more information.

**176F3373** **Bus Bar Mains, RFI, no fuse D2h/D4h****176F3371** **Bus Bar Mains, no Fuse, no RFI D2h/D4h**

Bus Bar Mains, no Fuse, no RFI D2h/D4h

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

**176F3370** [🔗](#)**Insulation Motor Terminals D2h/D4h**

Insulation Motor Terminals D2h/D4h

**176F3369** [🔗](#)**Insulation Mains Terminals D2h/D4h****176F3368** [🔗](#)**Bus Bar Motor Terminals U,V,W D2h/D4h****176F3367** [🔗](#)**IGBT Brake Module 650amp****176F3365** [🔗](#)**IGBT DUAL MODULE 900AMP T4/T5 DRIVE****176F3361** [🔗](#)**Bracket Inrush Support D2h/D4h****176F6634** [🔗](#)**CAPACITOR T5**

To be used on the following frame sizes

D-frame: Drives produced during or after week 18, 2018 with production site "H" indicated by the character preceding the last 3 characters of the serial number (H188)

E-frame: Any datecode

Image coming soon

176F5749 [🔗](#)**Enclosure Right Side D4h**

Image coming soon

176F5748 [🔗](#)**Top Plate Assembly D4h**

Image coming soon

176F5747 [🔗](#)**Enclosure Left Side D4h****For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

**176F5723** [🔗](#)**DC Link Coil Large Dh Frame 78uH**

DC Link Coil Large Dh Frame 78uH

**176F6520** [🔗](#)**Cable Power Card to CT D2h/D4h**

2015 yılının 51. haftasında veya sonrasında üretilen sürücülerde kullanım için.

**176F6447** [🔗](#)**Akım sensörü 500 A - FX10**

D2h, D4h, D7h ve D8h muhafaza boyutları:

DTC 302 - tümüyle uyumlu.

Tüm diğerleri - 2016 yılının 3. haftasında veya sonrasında üretilen sürücülerde kullanım için.

E1, E2, F1, F2, F3, F4, F8, F9, F10, F11, F12, F13, F18 muhafaza boyutları:

2016 yılının 16. haftasında veya sonrasında üretilen sürücülerde kullanım için.

**176F3180** [🔗](#)**Cable Brake IGBT Gate Signal D2h D4h****176F3178** [🔗](#)**Cable IGBT Temp to Gate PCA D2h D4h****176F3176** [🔗](#)**Cable IGBT Gate Signal D2h D4h****176F3167** [🔗](#)**Üst fan IP20 DC 80X38 48 VDC**

IP20,top fan, 80x38mm, 48VDC, fan only

**176F3165** [🔗](#)**Karıstırıcı fan DC 40X28 - 24 VDC**

Mixing fan, mounted below the input terminals

**176F3164** [🔗](#)**Heatsink Fan DC 172x51****For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

**176F3163** [🔗](#)**DC Bus CAP 4700uF 450V single in housing**

To be used on the following frame sizes

D-frame: Drives produced before week 18, 2018 with production site "H" indicated by the character preceding the last 3 characters of the serial number (H188)

**176F3162** [🔗](#)**IGBT snubber kon 1000 V 1,5 UF geniş mntj**

IGBT snubber cap, mounts on IGBT modules

**176F3161** [🔗](#)**Balance/HF Card NO 110-315kW 400V****176F3160** [🔗](#)**Gate Drive Card NO 110-315kW 400V****176F3159** [🔗](#)**Inrush Card NO 110-315kW 400V****176F3157** [🔗](#)**Akım ölçekleme kartı 5,10 ohm**

Installs on the power board

**176F3144** [🔗](#)**Power Card NO 250kW 380-500V**

Image
coming
soon

176F8430 [🔗](#)**Cable Clamp for frame size D & E****130B7530** [🔗](#)**Mounting Kit f. C Option, 40mm, A2/A3**

MCF 105 assembly kit A2 / A3 for C option



x10

130B9001 [🔗](#)**multiple 2 pole power combicon, 24V plug**

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

**130B5601** [🔗](#)**VLT® DeviceNet converter MCA194 kplımlı**

VLT® DeviceNet converter MCA194 coated

**130B0264** [🔗](#)**Cradle for A5,B1,B2,C1,C2,D2h enclosure**

cradle for LCP cradle for a5, b1,b2,c1,

**130B0295** [🔗](#)**Kontrol kartı giriřli aksesuar çantası****130B1069** [🔗](#)**Çoklu röle 1 fiř**

spare, 3 pole connector, relay 1, fc300

**130B1068** [🔗](#)**Çoklu röle 2 fiř**

spare, 3 pole connector, relay 2, fc300

**130B1107** [🔗](#)**VLT® Control Panel LCP 102**

VLT Control Panel LCP 102

Düz metinli, aydınlatmalı grafik ekran.

Tüm dilleri ve metin karakterlerini destekler.

Kısa sürede devreye alma için hızlı menü.

Parametre grupları içim kaydetme ve kopyalama işlevi.

Tüm işlevler için çevrimiçi yardım.

**130B1088** [🔗](#)**IP20/21 için Danfoss logolu LCP kör kpk.****134B1726** [🔗](#)**FC-302 için güvenli drřli kontrol kartı**

Yazılım versiyonu 8.12 veya üstü ile uyumludur. Sürücünüz müşteriye özel bir yazılıma veya marka etiketli bir yazılım versiyonuna sahipse, lütfen kontrol kartı parça numarası 130B1109 için sipariş verin.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

Image
coming
soon**176F6767****Bus Bar Assy Capbank Twist 400V D2h/D4h**

Aşağıdaki muhafaza boyutlarında kullanılmalıdır
"H" üretim tesisinde, 2018 yılının 18. haftasında veya sonrasında üretilen, D muhafaza boyutlu sürücülerde kullanım için. Üretim tesisi, seri numarasının son 3 karakterinin önündeki karakterle gösterilir (örneğin, H188).

**176F3880****FC302 Advanced Spare Pkg 200kW T5**

1 Qty 176F3159 Inrush Card NO 110-315kW 400V
1 Qty 176F3144 POWER CARD NO 250kW 380-500V
1 Qty 134B1726 Control Card for FC-302
3 Qty 176F3365 IGBT Dual Module 900amp T4/T5 Drive
1 Qty 176F3890 Retrofit kit for SCR 176F3860

**176F3879****FC302 Standard Spare Pkg 200kW T5**

1 Qty 176F3159 Inrush Card NO 110-315kW 400V
1 Qty 176F3144 POWER CARD NO 250kW 380-500V
1 Qty 134B1726 Control Card for FC-302

**176F6692****Alet, kondansatör sökme/takma**

Tool to remove DC bus caps

**134B5270****Alu.Box 750x550x380 Drivepro spare part**Image
coming
soon**134B5998****24 pole jumper/2 connector jumper****176F3890****568A SCR Retrofit Kit - N200T5/N250T5 HO**

Before ordering this part, please read product note 337 for details.
568A SCR Retrofit Kit - N200T5/N250T5 HO

Image
coming
soon**176F3860****Rectifier SCR/Diode 586A 1600V**

Before ordering this part, please read product note 337 for details.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

Image
coming
soon**176F6769** **Thermal Grease - Pack of 5****134B7466** **Option A Ethernet Package**Image
coming
soon**134B6883** **VLT Progr. Contr. MCB 301, coated****176F4183** **Bsbr Crnt Sensor D2h/D4h - 500A LEM, HEX****176F4106** **Fieldbus plate, highpower, IP20, 10 pcs****176F4195** **Current Sensor 500A LEM LF505**

This part is only used on products produced in Haiyan after week 41 2022

.

Please check that serial number has a "A" before the date code and that the date code is greater than or equal 000104A412

For detail about the change please read product note 409

**176F4197** **Current Sensor Cable D2 LEM LF505**

This part is only used on products produced in Haiyan after week 41 2022

.

Please check that serial number has a "A" before the date code and that the date code is greater than or equal 000104A412

For detail about the change please read product note 409

**130B1071** **6 Kutuplu Konektör, FC serisi, (10 adet)**

6-pole spring cage connectors 10 pcs

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

**134B9413** **Airflow Sensor KLQ CO2 & Air Quality**

DUCT AIR QUALITY (VOC) AND CO2 SENSOR KLQ-CO2-MB

Maintenance-free duct sensor covering air quality (VOC 0...100 %), carbon dioxide (CO2 0...5000 ppm) and atmospheric pressure (hPa). The air quality is detected by a VOC sensor (mixed gas sensor for volatile organic substances) and include an automatic calibration. It determines the loading of the room air due to contaminated gases such as cigarette smoke, body perspiration, exhaled breathing air, solvent vapors, emissions etc. The air contamination can be selected into different sensitivity ranges as low, medium or high. The CO2 measurement is performed using an optical NDIR sensor (non-dispersive infra-red technology), and the detection range is calibrated for standard applications such as monitoring residential rooms and conference rooms. A microprocessor-controlled solution with factory sensor calibration, Modbus RTU connection in a resistant IP65 plastic housing with mounting flange, quick-locking screws and two M16 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

VOC Sensor: Volatile Organic Compounds sensor (metal oxide) with automatic calibration

VOC measuring range: 0...100 % air quality; referred to calibrating gas & selection of VOC sensitivities (low/medium/high)

VOC measuring accuracy: typical $\pm 20\%$ of final value (referred to calibrating gas)

CO2 Sensor: optical NDIR sensor (non-dispersive infra-red technology) including atmospheric pressure compensation (up to 1100 mbar) with manual or automatic calibration

CO2 measuring range: 0...5000 ppm

CO2 measuring accuracy: typical ± 30 ppm ($\pm 3\%$ of measured value) & temperature dependence: ± 5 ppm pro $^{\circ}\text{C}$ or $\pm 0,5\%$ of measured value pro $^{\circ}\text{C}$ (whichever is higher) & pressure dependence: $\pm 0.13\%$ per mm Hg

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC/DC ($\pm 10\%$) 24DC $<1,6\text{W}$

Operation temperature: $-10...+60$ $^{\circ}\text{C}$ / $14...+140$ $^{\circ}\text{F}$

T2-IP65 plastic housing two M20 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**134G8893****FC-302N250T5E20H4BGR7XXSXXXXXAXBXCXXXXDX**

Frekans Knavertörü
FC-302N250T5E20H4BGR7XXSXXXXXAXBXCXXXXDX
VLT® AutomationDrive FC-302
(N250) 250 KW / 350 HP, Trifaze
380 - 500 VAC, IP 20 / Şasi
RFI sınıfı A1 (C2)
Fren kesici
Grafik Lokal Kontrol Panel
Kıplımlı PCB 3C3+Söğlmİştrİmlş, Sigorta
Son sürüm std. yazılım
Kasa Boyutu: D4H
C1 opsiyonu yok, D seçeneđi yok
A Seçeneđi Yok, B Seçeneđi Yok
Model Koduna göre diđer seçenekler

Model kodu: FC-302N250T5E20H4BGR7XXSXXXXXAXBXCXXXXDX

VLT® AutomationDrive, tüm standart veya servo makinelerde ya da üretim hatlarında tam kapsamlı operasyon kontrolü sunan tek bir sürücü konsepti oluşturur.

**130R1153****DrivePro Extended Warranty Servis Bayisi**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.
You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1156****DrivePro Extended Warranty Servis Bayisi**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.
You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1152****DrivePro ExWarr Work Shop PG06 36 months**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.
You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services



130R1154 [🔗](#)

DrivePro Extended Warranty Servis Bayisi

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.



130R1155 [🔗](#)

DrivePro Extended Warranty Servis Bayisi

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.



130R1151 [🔗](#)

DrivePro Extended Warranty Servis Bayisi

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.



130R1150 [🔗](#)

DrivePro Extended Warranty Servis Bayisi

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.



130R1157 [🔗](#)

DrivePro Extended Warranty Servis Bayisi

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.



130R1158 [🔗](#)

DrivePro Extended Warranty Servis Bayisi

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services



130R1057 [🔗](#)

DrivePro ExWarr Onsite PG06 66 months

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.



130R1056 [🔗](#)

DrivePro Extended Warranty sahada 60 ay

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.



130R1050 [🔗](#)

DrivePro Extended Warranty sahada 24 ay

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.



130R1058 [🔗](#)

DrivePro Extended Warranty sahada 72 ay

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.



130R1055 [🔗](#)

DrivePro Extended Warranty sahada 54 ay

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.



130R1053 [🔗](#)

DrivePro Extended Warranty sahada 42 ay

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**130R1054** [🔗](#)**DrivePro Extended Warranty sahada 48 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1052** [🔗](#)**DrivePro Extended Warranty sahada 36 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1051** [🔗](#)**DrivePro Extended Warranty sahada 30 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1325** [🔗](#)**DriveProStart-UP ctrl. IFT test medium**

DrivePro Start-Up Control interface testing medium frame unit

**130R1322** [🔗](#)**DrivePro Start-Up special applic. medium**

DrivePro Start-Up special applications medium frame unit

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**130R1315****DrivePro Start-Up 1 day on-demand medium**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and

ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

**130R1314****DrivePro Start-Up 1 day pre-order medium**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and

ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**130R1306****DrivePro Start-Up unit on-demand medium**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and

ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

**130R1305****DrivePro Start-Up unit pre-order medium**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and

ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

Image
coming
soon

130R1199 **DrivePro Site Assessment**

investments.

DrivePro® Site Assessment is designed by Danfoss Drives to assess and analyze the drives at your site for effective asset management with a view of their maintenance and their lifecycle conditions. This assessment helps you to maintain, plan and take investments to achieve the highest possible reliability and performance.

Our experts visit your site and collect the data on your drives. We evaluate the collected data and help you to have an overview of risk factors in combination of all the parameters visually inspected at site. We give you a report on key facts which would help your management to take decisions on maintenance, planning, renewals and on future investments.

**130R1382** **DrivePro Start-Up ½ day pre-order medi**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**130R1383** **DrivePro Start-Up ½ day on-demand medi**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and

ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

Image
coming
soon

130R1348 **DrivePro Remote Monitoring - Annual Fee**

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.