

**131B0542****FC-302P7K5T5E20H1XXXXXXXXXXA0BXCXXXXX**

Frekans Knavertörü

FC-302P7K5T5E20H1XXXXXXXXXXA0BXCXXXXX

VLT® AutomationDrive FC-302

7,5 kW / 10 HP, Trifaze

380 - 500 VAC, IP 20 / Şasi

RFI Sınıfı A1/B (C1)

Fren kesici yok

Lokal Kontrol Panel Yok

Kaplama PCB yok, Şebeke Seçeneği yok

Son sürüm std. yazılım

Kasa Boyutu: A3

C1 opsiyonu yok, D seçeneği yok

PROFIBUS DP MCA 101, B Seçeneği Yok

Model Koduna göre diğer seçenekler

Model kodu: FC-302P7K5T5E20H1XXXXXXXXXXA0BXCXXXXX

VLT® AutomationDrive, tüm standart veya servo makinelerde ya da üretim hatlarında tam kapsamlı operasyon kontrolü sunan tek bir sürücü konsepti oluşturur.

Verimlilik Verilerini Görüntüleme**PRODUCT DETAILS**

Brüt ağırlık		7.13 kg
Net ağırlık		6.6 kg
Hacim		27.246 l
EAN		5702427149212
VLT® AUTOMATIONDRIVE FC 300 SERIES		
Ürün Görünümü (Anahtar)	GLBL	Global (Standart)
Ürün Grubu	FC-	VLT® AutomationDrive FC-
Seri	302	302
Güç Değeri	P7K5	7,5 kW / 10 HP
Faz	T	Trifaze
Şebeke Voltajı	5	380 - 500 VAC
Muhafaza	E20	IP 20 / Şasi
RFI Filtresi	H1	RFI Sınıfı A1/B (C1)
Fren - Güvenli Duruş	X	Fren kesici yok
LCP	X	Lokal Kontrol Panel Yok
Kaplama PCB	X	Kaplama PCB yok
Şebeke Opsiyonu	X	Şebeke Seçeneği yok
Uyarlama A	X	Standart Kablo Girişleri
Uyarlama B	X	Uyarlama yok
Yazılım Sürümü	SXXX	Son sürüm std. yazılım
Yazılım Dil Paketi	X	Standart Dil Paketi
A Opsiyonu	A0	PROFIBUS DP MCA 101
B Opsiyonu	BX	B Seçeneği Yok
C0 Opsiyonu MCO	CX	C0 seçeneği yok
C1 Opsiyonu	X	C1 opsiyonu yok

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | FC-302P7K5T5E20H1XXXXXSXXXXA0BXCXXXXDX

PRODUCT DETAILS

C Opsiyon Yazılımı	XX	Yazılım seçeneği yok
D Opsiyonu	DX	D seçeneği yok
Kasa Boyutu	A3	A3
Tür Kodu Parça 1		FC-302P7K5T5E20H1XXX
Tür Kodu Parça 2		XXXXXXXA0BXCXXXXDX
Ürün Grubu	NO_VIEW	NO VIEW
Güç %160 (HO) [KW]		7.5
Yükseklik [mm]		268,0
C opsiyonu olm. genişlik [mm]		130,0
İki C opsiyonla genişlik [mm]		190,0
Derinlik [mm]		205,0
A/B opsiyonu ile Derinlik [mm]		220,0
kVA		11.1
Güç Kaybı HO [W]		225
Güç Kaybı HO [W]		225
Sürekli Akım (HO) [A]		16
Kesikli Akım (HO) [A]		25.6
Sürekli Akım (HO) [A]		14.5
Kesikli Akım (HO) [A]		23.2
Hesaplanan Brüt Ağırlık [kg]		7.13
Hes. Net Ağ. [kg]		6.6
ECCN EU		Y901
ECCN US		3A999.a
Satıcı	ERR01	Satıcı Belirlenmiyor
Fabrika Tarafından Önerilen	ERR01	Satıcı Belirlenmiyor
Modelkodu01		FC-302P7K5T5E20H1XXX
Modelkodu02		XXXXXXXA0BXCXXXXDX
Recommended Plant		ERR01

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Aksesuarlar

Image
coming
soon

130B3290 [🔗](#)**VLT® Safe option MCB 151, kaplamalı**

VLT® Safe option MCB 151, painted for HTL feedback, can be used up to PL d or SIL 2

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B3280** **VLT® Safe option MCB 150, kaplamalı**

Güvenlik modülleri; güvenliği artırmak, sistem maliyetlerini düşürmek, esnekliği artırmak ve üretkenliği iyileştirmek için makinelerin operatörlerle akıllı bir şekilde etkileşimde bulunmasını sağlar.

VLT® MCB 15x Safe opsiyonları, IEC 61800-5-2 işlevsel güvenlik standardına uygunluk için akıllı, kullanıcı dostu bir çözüm sunar ve kablolamayı azaltmaya yardımcı olur.

Yeni güvenlik modülü; ISO 13849-1 uyarınca PL d Kategorisi 3 ve IEC 61508 uyarınca SIL 2 sertifikalıdır.

**130B7635** **VLT® Lift Controller MCO 361**

Kaldırma uygulamasına yönelik özel yazılım içeren VLT® Motion Control MCO 305

**130B7531** **C Seçeneği için Montaj Kiti, 60mm, A2/A3**

VLT® Mounting kit for enclosure sizes A2 and A3.

Must be used when retrofitting 1 pc. of the following MCO options, together with MCB 113 Extended relay card (Located in MCO slot):

MCO 305 Programmable Motion Controller

MCO 350 Synchronizing Controller

MCO 351 Positioning controller

MCO 360 Salt Controller

MCO 361 Lift Controller

Product group: R

**130B7530** **Mounting Kit f. C Option, 40mm, A2/A3**

MCF 105 assembly kit A2 / A3 for C option



x10

130B7401 **NEMA 1 Conversion Kit, Top, 10 pcs, A3****130B7145** **VLT® SALT Controller MCO 360**

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B9860****VLT® Safety Option MCB152, kaplamalı**

Güvenlik opsiyonları; güvenliği artırmak, sistem maliyetlerini düşürmek, esnekliği artırmak ve üretkenliği iyileştirmek için makinelerin operatörlerle akıllı etkileşimde bulunmasını sağlar.

VLT® Safety Option MCB 152, IEC 61800-5-2 işlevsel güvenlik standardına uygunluk için akıllı, kullanıcı dostu bir çözüm sunar ve kablolamayı azaltmaya yardımcı olur. MCB 152, tehlikenin meydana geldiği yerden bağımsız olarak Güvenli Tork Kapatma (STO) özelliğinin etkinleştirilmesini sağlar. Yeni güvenlik opsiyonu; ISO 13849-1 uyarınca PL d Kategorisi 3 ve EN IEC 61508 uyarınca SIL 2 sertifikalıdır.

VLT® Safety Option MCB 152, VLT® PROFINET MCA 120 haberleşme opsiyonu ile VLT® AutomationDrive'in kontrol kartının kombinasyonu bir PROFIsafe aygıtı oluşturur.

**130B5645****Kaçak Akım İzleme Kiti, A2, A3****130B1234****VLT® Motion Control MCO 305, kaplamalı**

Integrated and programmable motion controller for VLT® AutomationDrive FC 301 and FC 302

- Adds additional functionality and flexibility as it is a freely programmable module
- Optimized for all types of positioning and synchronization applications
- Make your own program specially adapted to your application

Contains:

- synchronization (electronic shaft), positioning and electronic cam control
- 2 inputs support both stepwise and absolute encoders
- 1 encoder output (virtual master function)

10 digital inputs

- 8 digital outputs

- Sends and receives data via fieldbus interface (requires fieldbus option)

- PC software for programming and commissioning

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice.

Danfoss can offer help with programming / setting up MCO options.

Contact Danfoss for advice and prices.

Product group: R

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1227** **VLT® Resolver Input MCB 103, kaplamalı**

Resolver extension for FC 300. Enables the connection of the following

Resolver types:

Input voltage: 4..8 Vrms

Input frequency: 2.5..15 kHz

Number of resolver poles: 2 or 4

**130B1220** **VLT® Safe PLC I/O MCB 108, kaplamalı**

Increases security and helps you meet requirement security levels

- VLT® AutomationDrive FC 302 has a safety input based on a single pole 24 V DC input

- Security in a cost-effective way

Possibility of connection to two conductor safety system

Possibility to interrupt on the plus or minus side without disturbing the sensor signal

**130B1264** **VLT® Extended Relay Card MCB 113, kplımlı**

Daha fazla esneklik için 7 dijital giriş ve 2 analog çıkış ekler. 4 SPDT röle. NAMUR tavsiyelerine uygundur. Galvanik izolasyon olanağı.

**130B1253** **VLT® Position Controller MCO 351, kplımlı**

Extends the functional characteristics of the frequency converter in positioning applications

- Direct positioning via fieldbus, relative positioning, absolute positioning and touch probe positioning

- End stop handling (software and hardware)

- Mechanical brake handling (programmable hold delay)

Error handling

- Jog speed / manual operation

- None for programming, as it is pre-programmed

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice.

Danfoss can offer help with programming / setting up MCO options.

Contact Danfoss for advice and prices.

Product group: R

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1252****VLT® Synchronizing Ctrl. MCO 350, kplımlı**

MCO 350 - synchronous controller

Based on the MCO 305 prefabricated controller for Synchronization tasks. The adjustment takes place through parameter settings. Specific Programming skills are not required.

- 2 encoder inputs, both for incremental as well as absolute encoder
- 1 encoder output (virtual master function)
- 10 additional digital inputs
- 8 additional digital outputs
- fieldbus Communication (requires fieldbus card) with reinforced coating

**130B1172****VLT® Sensor Input Card MCB 114, kplasz**

Motordaki yatakların ve sargıların sıcaklığını izleyerek motoru aşırı ısınmaya karşı korur. 2 veya 3 telli PT100/PT1000 sensörler için üç adet otomatik algılamalı sensör girişi. Bir ek analog giriş 4-20 mA.

**130B1170****LCP Panel Montaj Kiti**

Kit; tespit elemanları ve conta içerir. LCP ve kablo içermez.

**130B1212****VLT® General Purpose I/O MCB 101, kplımlı**

MCB 101 - Advanced I / O option

Expands the number of freely programmable

Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.
 - 2 analog inputs 0 - 10 V.
 - 2 digital outputs NPN / PNP switchable 24 V
 - 1 analog output 0/4 - 20 mA
- with reinforced coating

**130B1210****VLT® Relay Option MCB 105, kaplamalı**

Relay extension for FC 100 and FC 300.

Extension with 3 additional load relays (changeover contacts),
easy to retrofit thanks to modular technology.

Painted version for harsh environments,
easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1208****VLT® 24V DC Supply MCB 107, kaplamalı**

Güç arızası sırasında kontrol bölümünü ve tüm kurulu opsiyonları çalışır durumda tutmak için harici bir DC beslemesi bağlayın. LCP'nin (parametre ayarı dahil) ve tüm kurulu opsiyonların şebeke bağlantısı olmadan tam olarak çalışmasını sağlar.

**130B1203****VLT® Encoder Input MCB 102, kaplamalı**

Çeşitli tiplerde artımlı ve mutlak enkoderleri bağlama imkanı sağlar. Bağlı enkoder, kapalı çevrim hız kontrolünün yanı sıra kapalı çevrim motor akısı kontrolü için kullanılabilir.

**130B1387****MCB107 Extern 24VDC Option FC300****130B1383****MCA101 Profibus Option DP V0/V1 FC300**

Krones acc. bag multipack 5pcs for A2/3-frame.

**130B1272****VLT® Sensor Input Card MCB114, kaplamalı**

MCB 114 - PT100 / PT1000 option

For FC100-FC200 and FC302 (painted version)

Enables the evaluation of up to 3 PT 100 or 3 PT 1000 sensors

- Connection of 2 and 3 wire sensors
- Automatic detection of the sensor type
- Additional 4-20mA input

**130B1164****VLT® Extended Relay Card MCB 113**

Daha fazla esneklik için 7 dijital giriş ve 2 analog çıkış ekler. 4 SPDT röle. NAMUR tavsiyelerine uygundur. Galvanik izolasyon olanağı.

**130B0185****Adaptör Plakası, 395x220 mm**

Adaptör plakası ile, FC sürücü için yeni delikler açmak zorunda kalmadan VLT® 5/6/8000'i bir FC sürücü ile değiştirebilirsiniz. Bu, VLT® 5/6/8000'i değiştirmeyi kolay ve hızlı hale getirir ve delik açılmayacağından elektrikli bileşenler için talaş hasarı söz konusu olmaz.

Aşağıdaki VLT® 5/6/8000, Adaptör Plakası 130B0185 üzerine monte edilebilir:

IP20 Kompakt: 200-240 Volt VLT5001-5006, 380/500 Volt VLT5001-5011

IP20/NM1: 200-240 Volt VLT6002-6005, 380/460 Volt VLT6002-6011, 380-480 Volt VLT8006-8011, 550-600 Volt VLT 5001-5011, 525-690 Volt VLT8002-8011

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar



130B0184

Adaptör Plakası, 395x130 mm

Adaptör plakası ile, FC sürücü için yeni delikler açmak zorunda kalmadan VLT® 5/6/8000'i bir FC sürücü ile değiştirebilirsiniz. Bu, VLT® 5/6/8000'i değiştirmeyi kolay ve hızlı hale getirir ve delik açılmayacağından elektrikli bileşenler için talaş hasarı söz konusu olmaz.

Aşağıdaki VLT® 5/6/8000, Adaptör Plakası 130B0184 üzerine monte edilebilir:

IP20 Kitabı: 200-240 Volt VLT5004-5006/VLT6004-6005, 380/500 Volt VLT5006-5011, 380-460 Volt VLT6006-6011



130B0058

Adaptör Plakası, 415x279 mm

Adaptör plakası ile, FC sürücü için yeni delikler açmak zorunda kalmadan VLT® 3000'i bir FC sürücü ile değiştirebilirsiniz. Bu, VLT® 3000'i değiştirmeyi kolay ve hızlı hale getirir ve delik açılmayacağından elektrikli bileşenler için talaş hasarı söz konusu olmaz.

Bir VLT® 3000'in çıkarıldığı yere C Opsiyonu olan ya da olmayan bir FC sürücü monte edilebilir.

Aşağıdaki VLT® 3000, Adaptör Plakası 130B0058 üzerine monte edilebilir:

IP20: 220/380/500 Volt VLT3002-3004 (frenli), 380/500 Volt VLT3006-3008 (frensiz)

IP21: 220/380/500 Volt VLT3002-3004 (frenli), 380/500 Volt VLT3006-3008 (frensiz)

IP54: 220 Volt VLT3002-3004 (frensiz), 220 Volt VLT3004 (frenli), 380/500 Volt VLT3002-3004 (frenli), 380/500 Volt VLT3002-3006 (frensiz)



130B1134

VLT® Motion Control MCO 305, kaplamasız

Integrated and programmable motion controller for VLT® AutomationDrive FC 301 and FC 302

- Adds additional functionality and flexibility as it is a freely programmable module
- Optimized for all types of positioning and synchronization applications
- Make your own program specially adapted to your application

Contains:

- synchronization (electronic shaft), positioning and electronic cam control
- 2 inputs support both stepwise and absolute encoders
- 1 encoder output (virtual master function)

10 digital inputs

8 digital outputs

- Sends and receives data via fieldbus interface (requires fieldbus Option)
- PC software for programming and commissioning.

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3.

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice. Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices.

Product group: R



130B1133

IP 21/Tip 1 dönüştürme kiti, üst, A3

Bu kitin yalnızca üst parçasıdır. Hem üst hem de alt parçası olan bir kite ihtiyacınız varsa lütfen

130B1123 siparişi verin.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1127****VLT® Resolver Input MCB 103, kaplamasız**

Motordan hız geri bildirimi sağlamak için bir çözümleyici bağlanmasına olanak verir. Yaylı bağlantı.

**130B1125****VLT® General Purpose I/O MCB 101, kplmsz**

MCB 101 - Advanced I / O option

Expands the number of freely programmable Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.
- 2 analog inputs 0 - 10 V.
- 2 digital outputs NPN / PNP switchable 24 V
- 1 analog output 0/4 - 20 mA

**130B1124****VLT® Control Panel LCP 101, nümerik**

Numerical control unit for FC 100 and FC 300. Allows access to all device parameters.

Quick menu for brief commissioning. Manual / auto switchover and alarm acknowledgment.

**130B1123****IP 21/Tip 1 dönüştürme kiti, A3**

Cover for housing size A3, type 1 MCF 101 NEMA1 / IP21

**130B1120****VLT® Safe PLC I/O MCB 108, kaplamasız**

Connection converter for FC 300 with control input for a safe stop. Allows secure connection.

Output modules with diagnostic pulse (Cross-circuit monitoring).

**130B1117****LCP Montaj Kiti, LCP'siz**

Kit; tespit elemanları, 3 m kablo ve conta içerir. LCP içermez.

**130B1115****VLT® Encoder Input MCB 102, kaplamasız**

Çeşitli tiplerde artımlı ve mutlak enkoderleri bağlama imkanı sağlar. Bağlı enkoder, kapalı çevrim hız kontrolünün yanı sıra kapalı çevrim motor akısı kontrolü için kullanılabilir.

**130B1114****Nümerik LCP101 ile LCP Montaj Kiti, 3 m**

Kit; nümerik LCP, tespit elemanları, 3 m kablo ve conta içerir.

**130B1113****Grafik LCP102 ile LCP Montaj Kiti, 3 m**

Kit; grafik LCP, tespit elemanları, 3 m kablo ve conta içerir.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**130B1112****Sub-D9 Adaptör kiti, A1, A2, A3**

SUB-D9 plug adapter for FC 100 and FC 300. Allows the use of SUB-D9 connectors at the Profibus DP interface.

**130B1110****VLT® Relay Option MCB 105, kaplamasız**

Relay extension for FC 100 and FC 300. Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A

**130B1153****VLT® Position Controller MCO351, kplmsz**

Extends the functional characteristics of the frequency converter in positioning applications

- Direct positioning via fieldbus, relative positioning, absolute positioning and touch probe positioning

- End stop handling (software and hardware)

- Mechanical brake handling (programmable hold delay)

Error handling

- Jog speed / manual operation

- None for programming, as it is pre-programmed

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice. Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices.

Product group: R

**130B1152****VLT® Synchronizing Contr. MCO350, kplmsz**

Senkronizasyon uygulamalarında VLT® AutomationDrive'in işlev özelliklerini genişletir ve geleneksel mekanik çözümlerin yerini alır. Hız senkronizasyonu. İşaretçi düzeltmeli ya da düzeltmesiz konum

(açı) senkronizasyonu. Çevrimiçi ayarlanabilir dişli oranı. Çevrimiçi ayarlanabilir konum (açı) ofseti. Birden fazla follower'ın senkronizasyonu için sanal master işlevine sahip enkoder çıkışı.

G/Ç'ler veya haberleşme üzerinden kontrol. Giriş işlevi. Sürücünün Lokal Kontrol Paneli aracılığıyla konfigürasyon olanağının yanı sıra durum ve veri okuma.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Akseuarlar

**130B1137****VLT® PTC Thermistor Card MCB 112, kplımlı**

ATEX: II (2) G [Ex eb Gb] [Ex db Gb] / II (2) D [Ex tb Db]

MCB 112 PTC - thermistor relay MS220DA In connection with ATEX certified explosion-proof motors for full motor protection. Certified PTC sensors are the sole protection required.

Integrable module with ATEX-compliant full thermal motor protection

1 PTB-certified PTC thermistor input

1 switch-off signal for using the Safe Stop function

1 logic output for error identification

**130B1077****IP55/67 için Danfoss logolu LCP kör kpk.**

LCP Blindcover IP66

**130B1071****6 Kutuplu Konektör, FC serisi, (10 adet)**

6-pole spring cage connectors 10 pcs

**130B1070****RS485 fiş, FC serisi, (10 adet)**

10pcs RS485 connectors for FC-series.

Product group: R

**130B1108****VLT® 24V DC Supply MCB 107, kaplamasız**

Güç arızası sırasında kontrol bölümünü ve tüm kurulu opsiyonları çalışır durumda tutmak için harici bir DC beslemesi bağlayın. LCP'nin (parametre ayarı dahil) ve tüm kurulu opsiyonların şebeke bağlantısı olmadan tam olarak çalışmasını sağlar.

**130B1107****VLT® Control Panel LCP 102**

VLT Control Panel LCP 102

Düz metinli, aydınlatmalı grafik ekran.

Tüm dilleri ve metin karakterlerini destekler.

Kısa sürede devreye alma için hızlı menü.

Parametre grupları içim kaydetme ve kopyalama işlevi.

Tüm işlevler için çevrimiçi yardım.

**130B1088****IP20/21 için Danfoss logolu LCP kör kpk.****175U0088****Montaj braketleri: Ayak izi, A1****For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**175U0086****Mont.: Brak.: Ayak izi,A3,2fren rez için**

Back frame A3 for 2 brake resistors

**175Z0929****LCP Kablosu, 3 m**

Cable for control panel (LCP), 3 meters

Works with the following LCP:

Alphanumeric control panel LCP3 - 175N0131

VLT® LCP 102 Graphic Display - 130B1107

VLT® LCP 101 Numeric Display - 130B1124

VLT® LCP 102 Graphic display IP66 - 130B1078

Product group: F1

Image
coming
soon**175U0009****Montaj braketi kiti, 216 x 30 x 18 mm**

Mounting angle for flatpack resistor 200W

**175N2584****VLT® EtherNet/IP MCA 121, kaplamalı**Image
coming
soon**134B5225****Uzak LCP ünitesi, 10 m**Remote mounting kit for LCP with cover for outdoor mounting with 10 m
(33 ft) cableImage
coming
soon**134B5224****Uzak LCP ünitesi, 5 m**Remote mounting kit for LCP with cover for outdoor mounting with 5 m (16
ft) cable**134B5223****Uzak Montaj Kiti LCP102, 3 m kablo ile**Remote mounting kit for LCP with cover for outdoor mounting with 3 m (10
ft) cable**For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B0460****LCP 103 Wireless Communication Panel**

With VLT® Wireless Communication Panel LCP 103 you can communicate with MyDrive® Connect - an app that can be downloaded for iOS and Android based smartphones. MyDrive® Connect makes commissioning easy, monitor and maintain tasks on your frequency converter. VLT® Wireless Communication Panel LCP 103 shows the current status of the drive (On, Warning, Alarm, Wifi connection) via built-in LED. Detailed information is also available using MyDrive® Connect. Here do you have access to i.a. status, menu and alerts. You can also see graphs over the latest available data.

The new VLT® Wireless Communication Panel LCP 103 allows you to wireless communication to the following drives:

- VLT® HVAC Drive FC 102
- VLT® Refrigeration Drive FC 103
- VLT® AQUA Drive FC 202
- VLT® AutomationDrive FC 302

[!]

Note!
LCP 103 only works on frequency converters produced in 2018 (White USB stik).

Product group: R1

Image
coming
soon

134B1992**Vida bağlantılı kontrol terminalleri****130B1266****VLT® MCB 115 Programlanab. G/Ç, kplımlı**

VLT® MCB 115 programmable I / O, coated

**134B6544****Gerçek Zamanlı Saat Seçeneği D, kaplımlı**

Opsiyon yalnızca 90 kW'a kadar olan sürücülerde MKII kontrol kartları ile desteklenir ve çalışır.

**130B0295****Kontrol kartı giriqli aksesuar çantası****130B1022****A2, A3 muh. boyutl. için aksesuar çant.**

Image
coming
soon

130B4847**extension cable for lcp+communication**

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B8492** [🔗](#)

Transducer 0-10g, 4-20mA; HS-22B50

**134B8493** [🔗](#)

Transducer 0-25mm/s RMS 4-20mA

CBM Transducer 0-25mm/s RMS 4-20mA

**134B8494** [🔗](#)

Transducer w, temp 0-25mm/s RMS 4-20mA

**134B8496** [🔗](#)

CABLE ASSY 10M, STRAIGHT SOCKET CONNETC.

Image
coming
soon**134B8497** [🔗](#)

Cable assy, M12 female connec.10m screen

Image
coming
soon**134B6883** [🔗](#)VLT Progr. Contr. MCB 301, coated

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9414****Antifreeze Thermostat FS20, 0/+15C**

TWO-PHASE FROST PROTECTION THERMOSTATS FS-20-UW

Electronic frost protection thermostat or frost monitor with switching relay output, continuous temperature and valve output (summation output 0–10 V) and control and cascading output (0–10 V), optionally with connection for a heating element. A IP65 resistant plastic housing with display with the actual temperature, measuring range, overrange/underrange of the set switch point (frost protection temperature) and alarm indicator for "frost" or "error" (capillary breakage, overvoltage/undervoltage), quick-locking screws and a fully active sensor rod made of copper. The delivery scope includes a set of MK-05-K mounting clamps for expert attachment of the sensor rod.

Measuring range: 0...+15 °C / 32...+59 °F

Accuracy: typical ± 1 K (at +10 °C)

Sensor type: 3m Copper rod active along the entire sensor length, min. response length of 25 cm

Input: 1 x 0 -10 V control input DDC & 1 x 0 -10 V cascading input

Output: 1 x 0 -10 V output temperature (corresponding to 0...+15 °C) & 1 x 0 -10 V output valve (frost signal with control voltage and cascading)

1 x potential-free changeover contact (24 V), range of adjustment 0...+15 °C

Current consumption: max. 100 mA at 24 V DC

Load resistance: $R_L > 50$ kOhm

Ambient temperature: –15...+50 °C / 5...+122 °F (Housing) & –20...+60 °C / –4...+140 °F Sensor and capillary tube > 20 cm from the housing.

Power: 24VAC/DC ($\pm 10\%$) 24DC <2,4W

T2-IP65 plastic housing with three-line display 70x40 mm (WxH), a M16 cable glands and MK-05-K mounting clamps.

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9413****Airflow Sensor KLQ CO2 & Air Quality**

DUCT AIR QUALITY (VOC) AND CO2 SENSOR KLQ-CO2-MB

Maintenance-free duct sensor covering air quality (VOC 0...100 %), carbon dioxide (CO2 0...5000 ppm) and atmospheric pressure (hPa). The air quality is detected by a VOC sensor (mixed gas sensor for volatile organic substances) and include an automatic calibration. It determines the loading of the room air due to contaminated gases such as cigarette smoke, body perspiration, exhaled breathing air, solvent vapors, emissions etc. The air contamination can be selected into different sensitivity ranges as low, medium or high. The CO2 measurement is performed using an optical NDIR sensor (non-dispersive infra-red technology), and the detection range is calibrated for standard applications such as monitoring residential rooms and conference rooms. A microprocessor-controlled solution with factory sensor calibration, Modbus RTU connection in a resistant IP65 plastic housing with mounting flange, quick-locking screws and two M16 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

VOC Sensor: Volatile Organic Compounds sensor (metal oxide) with automatic calibration

VOC measuring range: 0...100 % air quality; referred to calibrating gas & selection of VOC sensitivities (low/medium/high)

VOC measuring accuracy: typical ± 20 % of final value (referred to calibrating gas)

CO2 Sensor: optical NDIR sensor (non-dispersive infra-red technology) including atmospheric pressure compensation (up to 1100 mbar) with manual or automatic calibration

CO2 measuring range: 0...5000 ppm

CO2 measuring accuracy: typical ± 30 ppm (± 3 % of measured value) & temperature dependence: ± 5 ppm pro $^{\circ}\text{C}$ or $\pm 0,5$ % of measured value pro $^{\circ}\text{C}$ (whichever is higher) & pressure dependence: ± 0.13 % per mm Hg

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC/DC ($\pm 10\%$) 24DC $<1,6\text{W}$

Operation temperature: $-10...+60$ $^{\circ}\text{C}$ / $14...+140$ $^{\circ}\text{F}$

T2-IP65 plastic housing two M20 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9412****Airflow Sensor TF65 PT1000 Temperature**

DUCT TEMPERATURE SENSOR TF 65

The TF 65 temperature measuring transducer is a PT1000 class B resistance sensor with passive output. Measuring range from $-30...+150^{\circ}\text{C}$. In a resistant IP67 plastic housing and M16 cable gland for cable connection and a straight protective measuring tube and a mounting flange.

Sensor type: PT1000 class B (DIN EN 60751) 1000ohm at $0^{\circ}\text{C} \pm 0,3\text{ K}$ Measuring range: $-30...+150^{\circ}\text{C}$ / $-22...+302^{\circ}\text{F}$ Ambient temperature: $-20...+100^{\circ}\text{C}$ / $-4...+212^{\circ}\text{F}$ Testing current: $< 0.6\text{ mA}$ Insulating resistance: 100 M#, at $+20^{\circ}\text{C}$ (500V DC)

Connection type: 2-wire connection

Measuring tube: stainless steel, V4A (1.4571), $\varnothing 6\text{ mm}$, inserted length = 300 mm / 11.8 in

T1-IP67 plastic housing with a M16 cable glands and a mounting flange.

Housing dimensions: 72 x 64 x 37.8 mm / 2.83 x 2.52 x 1.49 in

**134B9411****Wall Sensor AFTF Temp & Humidity**

ON-WALL- HUMIDITY- AND TEMPERATURE SENSORS AFTF-MB

Calibratable outside humidity and temperature sensor AFTF, detect the relative humidity (0...100% RH) and the temperature ($-35...+80^{\circ}\text{C}$), including various parameters in the humidity measurement. Applied in clean air and non-aggressive, dust-free environment. With a Modbus connection in a resistant IP65 plastic housing and M20 cable gland for cable connection, with quick-locking screws and an exchangeable plastic sinter filter. International SI units (default) can be changed to imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / $-35...+80^{\circ}\text{C}$ (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical $\pm 2.0\%$ (20...80 % RH) at $+25^{\circ}\text{C}$, otherwise $\pm 3.0\%$

Deviation, temperature: typical $\pm 0.4\text{ K}$ at $+25^{\circ}\text{C}$ / $\pm 77^{\circ}\text{F}$ Zero point offset: $\pm 10\%$ RH (humidity) / $\pm 5^{\circ}\text{C}$ (temperature)Power: 24VAC ($\pm 20\%$) / 15...36VDC - 24DC $< 1,2\text{W}$ Operation temperature: $-30...+70^{\circ}\text{C}$ / $-22...+158^{\circ}\text{F}$

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9410****Wall Sensor ATM2 Temperature**

OUTSIDE / WET ROOM TEMPERATURE SENSOR ATM2-MB

Calibratable outside temperature sensor ATM2, PT1000 measure temperature (-50...+150 °C), with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M20 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

Sensor type: PT1000 class B (DIN EN 60751)

Measuring range: - 50...+150°C / -31... +176°F

Deviation: typical ± 0.2 K at +25 °C / ± 77 °F

Zero point offset: ± 10 °C / ± 50 °F

Ambient temperature: Measuring transducer -30...+70 °C / -22... +158°F

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC (± 20%) / 15...36VDC - 24DC <1,2W

Operation temperature: -30...+70 °C / -22...+158 °F

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

Image
coming
soon**134B9409****Airflow Sensor 8147 Temp&Humidity&7000Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS ±7000PA-MB

Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature (-35...+80 °C) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max. ± 7000 Pa) with connection nozzles for pressure hose (Ø 6 mm). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / - 35...+80°C / -31... +176°F (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical ± 2.0 % (20...80 % RH) at +25°C/+77°F , otherwise ± 3.0 %

Deviation, temperature: typical ± 0.2 K at +25 °C / ± 0.4 °F at +77 °F

Pressure range: ± 7000 Pa

Accuracy: 7000 Pa/28 inWC: typical ± 105 Pa at +25 °C / ± 0.12 inWC at + 77 °F

Above- # below-pressure: max. ± 50 kPa

Power: 24VAC (± 20%) / 15...36VDC - 24DC <0,2W

Operation temperature: -30...+70 °C / -22...+158 °F

Media temperature -20...+50 °C / -4...+122 °F IP65 plastic housing two

M16 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

Image
coming
soon**134B9408****Airflow Sensor 8148 Temp&Humidity&500Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS ± 500 Pa-MB
Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ($-35...+80$ °C) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max. ± 500 Pa) with connection nozzles for pressure hose ($\varnothing 6$ mm). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).
Measuring range: 0...100 % RH (humidity) / $-35...+80$ °C / $-31...+176$ °F (temperature)
Medium: clean air and non-aggressive, non-combustible gases
Deviation, humidity: typical ± 2.0 % (20...80 % RH) at $+25$ °C / $+77$ °F , otherwise ± 3.0 %
Deviation, temperature: typical ± 0.2 K at $+25$ °C / ± 0.4 °F at $+77$ °F
Pressure range: ± 500 Pa
Accuracy: 500 Pa/2.0 inWC: typical ± 13 Pa at $+25$ °C / ± 0.05 inWC at $+77$ °F
Above- # below-pressure: max. ± 50 kPa
Power: 24VAC (± 20 %) / 15...36VDC - 24DC $<0,2$ W
Operation temperature: $-30...+70$ °C / $-22...+158$ °F
Media temperature $-20...+50$ °C / $-4...+122$ °F IP65 plastic housing two M16 cable glands
Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9407****Airflow Sensor KFTF Temp & Humidity**

DUCT HUMIDITY- AND TEMPERATURE SENSORS KFTF-MB

Calibratable duct humidity and temperature sensor KFTF-T3 ($\pm 2.0\%$) with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection and a plastic sinter filter (exchangeable). Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ($-35...+80\text{ }^{\circ}\text{C}$) inside a tube, including various parameters in the humidity measurement. The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices.

International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / $-35...+80\text{ }^{\circ}\text{C}$ (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical $\pm 2.0\%$ (20...80 % RH) at $+25\text{ }^{\circ}\text{C}$, otherwise $\pm 3.0\%$

Deviation, temperature: typical $\pm 0.2\text{ K}$ at $+25\text{ }^{\circ}\text{C}$

Zero point offset: $\pm 10\%$ RH (humidity) / $\pm 5\text{ }^{\circ}\text{C}$ (temperature)

Power: 24VAC ($\pm 20\%$) / 15...36VDC - 24DC $<1,2\text{ W}$

Operation temperature: $-30...+70\text{ }^{\circ}\text{C}$ / $-22...+158\text{ }^{\circ}\text{F}$

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

**134B9406****Pressure Sensor 7227 2x7000Pa, Analog**DUAL AIR PRESSURE SENSOR $\pm 7000\text{ Pa}$ & $\pm 7000\text{ Pa}$, ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0-10 V or 4...20 mA.

Pressure range selection: $\pm 7000\text{ Pa}$ - 0...1000Pa / 2000Pa / 3000Pa / 5000Pa / 7000Pa

Accuracy: 7000 Pa typical $\pm 105\text{ Pa}$

Zero point offset: $\pm 10\%$ of measuring range

Above- # below-pressure: max. $\pm 50\text{ kPa}$

Power: 24VAC/DC ($\pm 10\%$) $<1,3\text{ W}$,

Output: automatically switching 0-10 V # 4...20 mA

Working resistance: $R_a\text{ (ohms)} = 25...450\text{ Ohm}$ (at I output)

Load resistance: $R_L > 15\text{ kOhm}$ (at U output)

Operation / Media temperature: $-20...+50\text{ }^{\circ}\text{C}$ / $-4...+122\text{ }^{\circ}\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9405****Pressure Sensor 7229 500/7000Pa, Analog**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 7000\text{Pa}$, ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA. Pressure range selection: $\pm 500\text{ Pa} - 0 \dots 100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$ Pressure range selection: $\pm 7000\text{ Pa} - 0 \dots 1000\text{Pa} / 2000\text{Pa} / 3000\text{Pa} / 5000\text{Pa} / 7000\text{Pa}$

Accuracy: 500 Pa typical $\pm 13\text{ Pa}$ Accuracy: 7000 Pa typical $\pm 105\text{ Pa}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ Power: 24VAC/DC ($\pm 10\%$) $< 1,3\text{W}$,

Output: automatically switching 0–10 V # 4...20 mA

Working resistance: $R_a\text{ (ohms)} = 25 \dots 450\text{ Ohm}$ (at I output)Load resistance: $R_L > 15\text{ kOhm}$ (at U output)Operation / Media temperature: $-20 \dots +50\text{ }^\circ\text{C} / -4 \dots +122\text{ }^\circ\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**134B9404****Pressure Sensor 7225 2x500Pa, Analog**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 500\text{Pa}$, ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA. Pressure range selection: $\pm 500\text{ Pa} - 0 \dots 100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$

Accuracy: 500 Pa typical $\pm 13\text{ Pa}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ Power: 24VAC/DC ($\pm 10\%$) $< 1,3\text{W}$,

Output: automatically switching 0–10 V # 4...20 mA

Working resistance: $R_a\text{ (ohms)} = 25 \dots 450\text{ Ohm}$ (at I output)Load resistance: $R_L > 15\text{ kOhm}$ (at U output)Operation / Media temperature: $-20 \dots +50\text{ }^\circ\text{C} / -4 \dots +122\text{ }^\circ\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Aksesuarlar

**134B9402****Pressure Sensor 7247T 2x7000Pa & PT1000**DUAL AIR PRESSURE SENSOR $\pm 7000\text{Pa}$ & $\pm 7000\text{Pa-MB}$

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ($-50\dots+150^\circ\text{C}$). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range: $\pm 7000\text{ Pa}$ and $\pm 7000\text{ Pa}$ Accuracy: $7000\text{ Pa}/28\text{ inWC}$: typical $\pm 105\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.12\text{ inWC}$ at $+77^\circ\text{F}$ Linearity: $< \pm 1\%$ of final value & Temperature drift: $\pm 0.1\%$ per $^\circ\text{C}$ / $^\circ\text{F}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ / $\pm 200\text{ inWC}$ Power: 24VAC ($\pm 20\%$) $<0,2\text{W}$ / $15\dots36\text{VDC}$ Operation temperature: $-30\dots+70^\circ\text{C}$ / $-22\dots+158^\circ\text{F}$ Media temperature $-20\dots+50^\circ\text{C}$ / $-4\dots+122^\circ\text{F}$

T2-IP65 plastic housing with two M16 cable glands & one M12 for temperature

Housing dimensions: $126 \times 90 \times 50\text{ mm}$ / $4.96 \times 3.54 \times 1.97\text{ in}$ **134B9401****Pressure Sensor 7249T 500/7000Pa & PT1000**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 7000\text{Pa-MB}$

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ($-50\dots+150^\circ\text{C}$). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range: $\pm 500\text{ Pa}$ and $\pm 7000\text{ Pa}$ Accuracy: $500\text{ Pa}/2.0\text{ inWC}$: typical $\pm 13\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.05\text{ inWC}$ at $+77^\circ\text{F}$ Accuracy: $7000\text{ Pa}/28\text{ inWC}$: typical $\pm 105\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.12\text{ inWC}$ at $+77^\circ\text{F}$ Linearity: $< \pm 1\%$ of final value & Temperature drift: $\pm 0.1\%$ per $^\circ\text{C}$ / $^\circ\text{F}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ / $\pm 200\text{ inWC}$ Power: 24VAC ($\pm 20\%$) $<0,2\text{W}$ / $15\dots36\text{VDC}$ Operation temperature: $-30\dots+70^\circ\text{C}$ / $-22\dots+158^\circ\text{F}$ Media temperature $-20\dots+50^\circ\text{C}$ / $-4\dots+122^\circ\text{F}$

T2-IP65 plastic housing with two M16 cable glands & one M12 for temperature

Housing dimensions: $126 \times 90 \times 50\text{ mm}$ / $4.96 \times 3.54 \times 1.97\text{ in}$ **For more information, please use this link to visit the product page on Danfoss Product Store**

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Akseuarlar

**134B9400****Pressure Sensor 7245T 2x500Pa & PT1000**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 500\text{Pa-MB}$

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ($-50\dots+150^\circ\text{C}$). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range: $\pm 500\text{ Pa}$ and $\pm 500\text{ Pa}$ Accuracy: $500\text{ Pa}/2.0\text{ inWC}$: typical $\pm 13\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.05\text{ inWC}$ at $+77^\circ\text{F}$ Linearity: $< \pm 1\%$ of final value & Temperature drift: $\pm 0.1\%$ per $^\circ\text{C}/^\circ\text{F}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove-/below-pressure: max. $\pm 50\text{ kPa}$ / $\pm 200\text{ inWC}$ Power: 24VAC ($\pm 20\%$) $< 0.2\text{W}$ / $15\dots 36\text{VDC}$ Operation temperature: $-30\dots+70^\circ\text{C}$ / $-22\dots+158^\circ\text{F}$ Media temperature $-20\dots+50^\circ\text{C}$ / $-4\dots+122^\circ\text{F}$

T2-IP65 plastic housing with two M16 cable glands & one M12 for temperature

Housing dimensions: $126 \times 90 \times 50\text{ mm}$ / $4.96 \times 3.54 \times 1.97\text{ in}$ **130B5601****VLT® DeviceNet converter MCA194 kplml**

VLT® DeviceNet converter MCA194 coated

Yedek parçalar

**130B7530****Mounting Kit f. C Option, 40mm, A2/A3**

MCF 105 assembly kit A2 / A3 for C option



x10

130B9001**multiple 2 pole power combicon, 24V plug****130B5601****VLT® DeviceNet converter MCA194 kplml**

VLT® DeviceNet converter MCA194 coated

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

**130B1200** **VLT® Profibus DP V1 MCA 101, kaplamalı**

Geniş çaplı uyumluluk, yüksek düzeyde kullanılabilirlik, tüm büyük PLC sağlayıcıları için destek ve gelecekteki versiyonlarla uyumluluk sağlar. Hızlı, verimli iletişim, şeffaf kurulum, gelişmiş arıza bulma ve parametrelendirme ile GSD dosyası kullanarak süreç verilerinin otomatik konfigürasyonu. PROFIBUS DP-V1, -PROFIdrive veya Danfoss FC profili durum makineleri, PROFIBUS DP-V1, Master Sınıf 1 ve 2 kullanarak çevrimsiz parametrelendirme.

**130B1012** **A1-A3 için terminal kapağı, seçenekli****130B1008** **LCP Kont. Tabanı için çerç., seçenekli****130B1022** **A2, A3 muh. boyutl. için aksesuar çant.****130B0295** **Kontrol kartı girişli aksesuar çantası**

Image
coming
soon

130B1075 **Profibus/BacNet 5 pimli konektör**

x10

130B1073 **10 Kutuplu konektör (10 adet)**

x10

130B1072 **8 Kutuplu konektör (10 adet)****130B1069** **Çoklu röle 1 fiş**

spare, 3 pole connector, relay 1, fc300

**130B1068** **Çoklu röle 2 fiş**

spare, 3 pole connector, relay 2, fc300

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | FC-302P7K5T5E20H1XXXXXXXXSXXXXA0BXCXXXXDX

Yedek parçalar

**130B1067** [🔗](#)

Çoklu bükümsüz şebeke fişi

**130B1064** [🔗](#)

Fren ve yük paylaşımı için term. bloku

Fren ve yük paylaşımı için terminal bloku

**130B1097** [🔗](#)

Fan grubu 80x80x25 mm kaplamalı

**130B1088** [🔗](#)

IP20/21 için Danfoss logolu LCP kör kpk.

**134B0286** [🔗](#)

EMC Shield A2, A3

**134B1726** [🔗](#)

FC-302 için güvenli drşl kontrol kartı

Yazılım versiyonu 8.12 veya üstü ile uyumludur. Sürücünüz müşteriye özel bir yazılıma veya marka etiketli bir yazılım versiyonuna sahipse, lütfen kontrol kartı parça numarası 130B1109 için sipariş verin.

**134B1975** [🔗](#)

Fieldbus kabloları için dekuplaj plakası

**130B1383** [🔗](#)

MCA101 Profibus Option DP V0/V1 FC300

Krones acc. bag multipack 5pcs for A2/3-frame.

Image
coming
soon**134B5998** [🔗](#)

24 pole jumper/2 connector jumper

Image
coming
soon**134B6883** [🔗](#)

VLT Progr. Contr. MCB 301, coated

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Yedek parçalar

**130B1071****6 Kutuplu Konektör, FC serisi, (10 adet)**

6-pole spring cage connectors 10 pcs

**134B9413****Airflow Sensor KLQ CO2 & Air Quality**

DUCT AIR QUALITY (VOC) AND CO2 SENSOR KLQ-CO2-MB

Maintenance-free duct sensor covering air quality (VOC 0...100 %), carbon dioxide (CO2 0...5000 ppm) and atmospheric pressure (hPa). The air quality is detected by a VOC sensor (mixed gas sensor for volatile organic substances) and include an automatic calibration. It determines the loading of the room air due to contaminated gases such as cigarette smoke, body perspiration, exhaled breathing air, solvent vapors, emissions etc. The air contamination can be selected into different sensitivity ranges as low, medium or high. The CO2 measurement is performed using an optical NDIR sensor (non-dispersive infra-red technology), and the detection range is calibrated for standard applications such as monitoring residential rooms and conference rooms. A microprocessor-controlled solution with factory sensor calibration, Modbus RTU connection in a resistant IP65 plastic housing with mounting flange, quick-locking screws and two M16 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

VOC Sensor: Volatile Organic Compounds sensor (metal oxide) with automatic calibration

VOC measuring range: 0...100 % air quality; referred to calibrating gas & selection of VOC sensitivities (low/medium/high)

VOC measuring accuracy: typical ± 20 % of final value (referred to calibrating gas)

CO2 Sensor: optical NDIR sensor (non-dispersive infra-red technology) including atmospheric pressure compensation (up to 1100 mbar) with manual or automatic calibration

CO2 measuring range: 0...5000 ppm

CO2 measuring accuracy: typical ± 30 ppm (± 3 % of measured value) & temperature dependence: ± 5 ppm pro $^{\circ}\text{C}$ or $\pm 0,5$ % of measured value pro $^{\circ}\text{C}$ (whichever is higher) & pressure dependence: ± 0.13 % per mm Hg

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC/DC ($\pm 10\%$) 24DC $<1,6\text{W}$

Operation temperature: $-10...+60$ $^{\circ}\text{C}$ / $14...+140$ $^{\circ}\text{F}$

T2-IP65 plastic housing two M20 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**131B0052****FC-302P7K5T5E20H1BGXXXXXSXXXXAXBXXXXDX**

Frekans Kvertörü

FC-302P7K5T5E20H1BGXXXXXSXXXXAXBXXXXDX

VLT® AutomationDrive FC-302

7,5 kW / 10 HP, Trifaze

380 - 500 VAC, IP 20 / Şasi

RFI Sınıfı A1/B (C1)

Fren kesici

Grafik Lokal Kontrol Panel

Kaplama PCB yok, Şebeke Seçeneği yok

Son sürüm std. yazılım

Kasa Boyutu: A3

C1 opsiyonu yok, D seçeneği yok

A Seçeneği Yok, B Seçeneği Yok

Model Koduna göre diğer seçenekler

Model kodu: FC-302P7K5T5E20H1BGXXXXXSXXXXAXBXXXXDX

VLT® AutomationDrive, tüm standart veya servo makinelerde ya da üretim hatlarında tam kapsamlı operasyon kontrolü sunan tek bir sürücü konsepti oluşturur.

**130R1121****DrivePro Extended Warranty Servis Bayisi**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1120****DrivePro Extended Warranty Servis Bayisi**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1122****DrivePro ExWarr Work Shop PG03 36 months**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**130R1123** **DrivePro Extended Warranty Servis Bayisi**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1126** **DrivePro Extended Warranty Servis Bayisi**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1125** **DrivePro Extended Warranty Servis Bayisi**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1124** **DrivePro Extended Warranty Servis Bayisi**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1127** **DrivePro ExWarr Work Shop PG03 66 months**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1128** **DrivePro Extended Warranty Servis Bayisi**

DrivePro® Standard Extended Warranty provides repair at a Danfoss Drives workshop, or shipment of a replacement product to the site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**130R1024** **DrivePro Extended Warranty sahada 48 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1025** **DrivePro Extended Warranty sahada 54 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1020** **DrivePro Extended Warranty sahada 24 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1022** **DrivePro Extended Warranty sahada 36 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1021** **DrivePro ExWarr Onsite PG03 30 months**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1027** **DrivePro Extended Warranty sahada 66 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**130R1026** **DrivePro® Extended Warranty sahada 60 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1028** **DrivePro® Extended Warranty sahada 72 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1023** **DrivePro® Extended Warranty sahada 42 ay**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1303** **DrivePro Start-Up unit pre-order small**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and

ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

**130R1324** **DrivePro Start-Up ctrl. IFT test small**

DrivePro Start-Up Control interface testing small frame unit

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**130R1321** **DrivePro Start-Up special applic. small**

DrivePro Start-Up special applications small frame unit

**130R1313** **DrivePro Start-Up 1 day on-demand small**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

**130R1312** **DrivePro Start-Up 1 Day Pre-order small**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services



130R1304

DrivePro Start-Up unit on-demand small

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and

ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

Image
coming
soon

130R1199

DrivePro Site Assessment

investments.

DrivePro® Site Assessment is designed by Danfoss Drives to assess and analyze the drives at your site for effective asset management with a view of their maintenance and their lifecycle conditions. This assessment helps you to maintain, plan and take investments to achieve the highest possible reliability and performance.

Our experts visit your site and collect the data on your drives. We evaluate the collected data and help you to have an overview of risk factors in combination of all the parameters visually inspected at site. We give you a report on key facts which would help your management to take decisions on maintenance, planning, renewals and on future investments.

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Services

**130R1380** **DrivePro Start-Up ½ day pre-order small**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and

ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

**130R1381** **DrivePro Start-up ½ day on-demand small**

DrivePro® Start-up gives the Customer a full range of checks and adjustments during commissioning of the drive, ensuring their system is tuned for optimal performance right from day one.

The following benefits can be gained:

- Installation is checked to ensure it complies to Danfoss guide lines.
- The AC drive is fine-tuned specific to the application, ensuring optimal performance.
- Maximum energy savings to the Customer.
- Extend the AC drive's lifespan.
- Report detailing findings.

Before DrivePro® Start-up can be implemented, the AC drive must be installed and

ready for operation. The entire system must be fully operational under normal operation conditions. Installation of the drive is not included in this package. Commissioning needs to take place during the standard working hours.

General Terms and Conditions of Delivery and Warranty apply.

Image
coming
soon

130R1348 **DrivePro Remote Monitoring - Annual Fee**

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.