




---

 PRODUCT-DETAILS

## ACQ580-01-062A-4

LV AC wall-mounted drive for water and wastewater, IEC: Pn 30 kW, 62 A, 400 V (ACQ580-01-062A-4)




---

### General Information

Global Commercial Alias	ACQ580-01-062A-4
Product ID	3AXD50000034599
ABB Type Designation	ACQ580-01-062A-4
EAN	6438177409854

Catalog Description	LV AC wall-mounted drive for water and wastewater, IEC: Pn 30 kW, 62 A, 400 V (ACQ580-01-062A-4)
---------------------	--

#### Long Description

The ACQ580-01 drives deliver innovative pump features for the water and wastewater industry, securing energy efficient flow of water and wastewater in your pumping solutions. This robust and compact wall-mounted drive has built-in pump application functionality such as sensorless flow calculation, multipump control, level control, soft pipe fill, dry run protection, quick ramps and a solution for keeping the impeller of the pump clean.

Usability is further enhanced with the intuitive Hand-Off-Auto control panel, the PC tool Drive composer and an optional Bluetooth® control panel. The built-in energy calculator visualizes the energy savings achieved with the use of the drive. The ACQ580-01 variant comes in IP21 enclosure as standard and can be installed on the wall. Also, IP55 and flange mounting units are available.

---

### Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044086
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACQ580-01-062A-4 PN: 30 kW, IN: 62 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

## Dimensions

Product Net Weight	20 kg 42 lb
Product Net Depth / Length	257 mm 10.118 in
Product Net Height	636 mm 25.039 in
Product Net Width	203 mm 7.992 in
Package Level 1 Depth / Length	794 mm 31.26 in
Package Level 1 Height	358 mm 14.09 in
Package Level 1 Width	278 mm 10.95 in
Package Level 1 Units	1 carton

## Technical

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	4000 m 5 ... 95
Power Factor	0.98
Sound dB (A)	70 dB(A)
Multiple Battery Information	Lithium Coin; CR2032; 220 mAh; 3 V; 1 pc; 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R4
Input Voltage (U <sub>in</sub> )	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0

	RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Normal Use ( $I_n$ )	62 A
Output Current, Light-Overload Use ( $I_{LD}$ )	58 A
Output Current, Heavy-Duty Use ( $I_{HD}$ )	45 A
Output Power, Normal Use ( $P_n$ )	30 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	30 kW
Output Power, Heavy-Duty Use ( $P_{HD}$ )	22 kW
Apparent Power Output	43 kV·A
Efficiency Level	IE2
Standby Loss	19 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	247 W	90.2 %	0.6 %
0/50 %	322 W	93.2 %	0.7 %
0/100 %	574 W	93.8 %	1.3 %
50/25 %	270 W	94.6 %	0.6 %
50/50 %	370 W	96.1 %	0.9 %
50/100 %	683 W	96.4 %	1.6 %
90/50 %	430 W	97.5 %	1.0 %
90/100 %	873 W	97.4 %	2.0 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

## External Classifications and Standards

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

## Environmental

SCIP	596c7575-1ed1-48e9-be9a-d8fdd900606b Finland (FI)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

---

## Additional Information

---

Product Name

Frequency converter

---

---

## Categories

---

Drives → Low Voltage AC Drives → Industry-Specific Drives → Drives for Water → ACQ580-01 - Wall-mounted drive for water and wastewater

